

Heisener.com

ETSA190342UC-P6RP-SZ

ETSA190342UC-P6RP-SZ Information

Part Number ETSA190342UC-P6RP-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 19V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ETSA190342UC-P6RP-SZ Specifications

Manufacturer Part Number ETSA190342UC-P6RP-SZ Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series ETSA-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ETSA-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Manufacturer Part Number	ETSA190342UC-P6RP-SZ
Package - Series ETSA-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Manufacturer	CUI Inc.
Package - Series ETSA-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesETSA-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input85 ~ 264 VACVoltage - Output19VCurrent - Output (Max)3.42APower (Watts)60WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Series	ETSA-U
Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 19V Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 4.57 " L x 1.97 " W x 1.22 " H (116.0mm x 50.0mm x 31.0mm)	Region Utilized	North America
Voltage - Input 85 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.42A Power (Watts) No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 19V 3.42A 60W Cow Commercial Positive Center ITE (Commercial) Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Input Type	Cord
Current - Output (Max) 3.42A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Voltage - Input	85 ~ 264 VAC
Power (Watts) $60W$ No Load Power Consumption $300mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 4.57 " L x 1.97 " W x 1.22 " H ($116.0mm$ x $50.0mm$ x $31.0mm$)	Voltage - Output	19V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$	Current - Output (Max)	3.42A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$	Power (Watts)	60W
Applications ITE (Commercial) Efficiency Level V Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57° L x 1.97° W x 1.22° H (116.0 mm x 50.0 mm x 31.0 mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \text{ x } 1.97^{\circ}\text{ W x } 1.22^{\circ}\text{H} (116.0\text{mm x } 50.0\text{mm x } 31.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Efficiency	Level V
Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)
		Report errors?

ETSA190342UC-P6RP-SZ Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ETSA190342UC-P6RP-SZ Payment Methods





















ETSA190342UC-P6RP-SZ Shipping Methods













If you have any question about ETSA190342UC-P6RP-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com