

Heisener.com

# ETSA240270UC-P6RP-SZ

### ETSA240270UC-P6RP-SZ Information

Part Number ETSA240270UC-P6RP-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 24V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# ETSA240270UC-P6RP-SZ Specifications

Manufacturer Part Number         ETSA240270UC-P6RP-SZ           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         ETSA-U           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         85 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         2.7A           Power (Watts)         60W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         ETSA-U           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         85 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         2.7A           Power (Watts)         60W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Manufacturer Part Number	ETSA240270UC-P6RP-SZ
Package         -           Series         ETSA-U           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         85 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         2.7A           Power (Watts)         60W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Manufacturer	CUI Inc.
Package         -           Series         ETSA-U           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         85 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         2.7A           Power (Watts)         60W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesETSA-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input85 ~ 264 VACVoltage - Output24VCurrent - Output (Max)2.7APower (Watts)60WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output $24\text{V}$ Current - Output (Max) $2.7\text{A}$ Power (Watts) $60\text{W}$ No Load Power Consumption $300\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $2.5\text{mm}$ I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension $4.57$ " L $x 1.97$ " W $x 1.22$ " H ( $116.0\text{mm}$ x $50.0\text{mm}$ x $31.0\text{mm}$ )	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Series	ETSA-U
Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output $24\text{V}$ Current - Output (Max) $2.7\text{A}$ Power (Watts) $60\text{W}$ No Load Power Consumption $300\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $2.5\text{mm}$ I.D. $\times 5.5\text{mm}$ O.D. $\times 9.5\text{mm}$ Size / Dimension $4.57$ " L $\times 1.97$ " W $\times 1.22$ " H ( $116.0\text{mm} \times 50.0\text{mm} \times 31.0\text{mm}$ )	Region Utilized	North America
Voltage - Input  85 ~ 264 VAC  Voltage - Output  24V  Current - Output (Max)  2.7A  Power (Watts)  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 2.7A  Power (Watts) 60W  No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Input Type	Cord
Current - Output (Max)  2.7A  Power (Watts)  60W  No Load Power Consumption  300mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Voltage - Input	85 ~ 264 VAC
Power (Watts) $60W$ No Load Power Consumption $300mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $4.57$ " L x $1.97$ " W x $1.22$ " H ( $116.0mm$ x $50.0mm$ x $31.0mm$ )	Voltage - Output	24V
No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$	Current - Output (Max)	2.7A
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$	Power (Watts)	60W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}$ C ~ $40^{\circ}$ C  Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.57^{\circ}$ L x $1.97^{\circ}$ W x $1.22^{\circ}$ H ( $116.0$ mm x $50.0$ mm x $31.0$ mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0\text{mm} \times 50.0\text{mm} \times 31.0\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Efficiency	Level V
Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)
		Report errors?

### ETSA240270UC-P6RP-SZ Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## ETSA240270UC-P6RP-SZ Payment Methods



















## ETSA240270UC-P6RP-SZ Shipping Methods













If you have any question about ETSA240270UC-P6RP-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com