

ETSA240625U-P51-WP

ETSA240625U-P51-WP Information



For Reference Only

Part Number ETSA240625U-P51-WP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 150W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ETSA240625U-P51-WP Specifications

Manufacturer Part Number ETSA240625U-P51-WP Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series ETSA-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.25A Power (Watts) 150W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ETSA-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.25A Power (Watts) 150W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Manufacturer Part Number	ETSA240625U-P51-WP
Package-SeriesETSA-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)6.25APower (Watts)150WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Manufacturer	CUI Inc.
Package - Series ETSA-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.25A Power (Watts) 150W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesETSA-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)6.25APower (Watts)150WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)6.25APower (Watts)150WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Package	-
FormDesktop (Class I)Input Type $Cord$ (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 6.25A Power (Watts) 150W No Load Power Consumption 500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ}\text{ W} \times 1.73^{\circ}\text{ H} (170.0\text{mm} \times 85.0\text{mm} \times 44.0\text{mm})$	Series	ETSA-U
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.25A Power (Watts) 150W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 6.25A Power (Watts) 150W No Load Power Consumption 500mW (Max) Polarization $-$ Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ}\text{W} \times 1.73^{\circ}\text{H} (170.0\text{mm} \times 85.0\text{mm} \times 44.0\text{mm})$	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 6.25A Power (Watts) 150W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 6.25A Power (Watts) 150W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $150W$ No Load Power Consumption $500mW$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorPower DIN, 4 PinSize / Dimension 6.69 " L x 3.35 " W x 1.73 " H (170.0mm x 85.0 mm x 44.0 mm)	Voltage - Output	24V
No Load Power Consumption 500mW (Max) Polarization - ITE (Commercial) Efficiency Level VI Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Power DIN, 4 Pin Size / Dimension 6.69° L x 3.35° W x 1.73° H (170.0mm x 85.0 mm x 44.0 mm)	Current - Output (Max)	6.25A
Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ} \text{W} \times 1.73^{\circ} \text{H} (170.0 \text{mm} \times 85.0 \text{mm} \times 44.0 \text{mm})$	Power (Watts)	150W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Power DIN, 4 Pin Size / Dimension 6.69° L x 3.35° W x 1.73° H (170.0mm x 85.0 mm x 44.0 mm)	No Load Power Consumption	500mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.69^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0\text{mm x } 85.0\text{mm x } 44.0\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $6.69^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0\text{mm x } 85.0\text{mm x } 44.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Efficiency	Level VI
Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)
		Report errors?

ETSA240625U-P51-WP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ETSA240625U-P51-WP Payment Methods



















ETSA240625U-P51-WP Shipping Methods













If you have any question about ETSA240625U-P51-WP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com