

## ETSA240625U-P51-WP

### ETSA240625U-P51-WP Information



For Reference Only

Part Number ETSA240625U-P51-WP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 24V 150W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## ETSA240625U-P51-WP Specifications

Manufacturer Part Number         ETSA240625U-P51-WP           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         ETSA-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         6.25A           Power (Watts)         150W           No Load Power Consumption         500mW (Max)           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 60°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         ETSA-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         6.25A           Power (Watts)         150W           No Load Power Consumption         500mW (Max)           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 60°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Manufacturer Part Number	ETSA240625U-P51-WP
Package-SeriesETSA-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)6.25APower (Watts)150WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Manufacturer	CUI Inc.
Package         -           Series         ETSA-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         6.25A           Power (Watts)         150W           No Load Power Consumption         500mW (Max)           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 60°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesETSA-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)6.25APower (Watts)150WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)6.25APower (Watts)150WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Package	-
FormDesktop (Class I)Input Type $Cord$ (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $24\text{V}$ Current - Output (Max) $6.25\text{A}$ Power (Watts) $150\text{W}$ No Load Power Consumption $500\text{mW}$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ}\text{ W} \times 1.73^{\circ}\text{ H} (170.0\text{mm} \times 85.0\text{mm} \times 44.0\text{mm})$	Series	ETSA-U
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 6.25A  Power (Watts) 150W  No Load Power Consumption 500mW (Max)  Polarization -  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 60°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $24\text{V}$ Current - Output (Max) $6.25\text{A}$ Power (Watts) $150\text{W}$ No Load Power Consumption $500\text{mW}$ (Max)  Polarization $-$ Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ}\text{W} \times 1.73^{\circ}\text{H} (170.0\text{mm} \times 85.0\text{mm} \times 44.0\text{mm})$	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max) 6.25A  Power (Watts) 150W  No Load Power Consumption 500mW (Max)  Polarization - Applications ITE (Commercial)  Efficiency Operating Temperature 0°C ~ 60°C  Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 6.25A  Power (Watts) 150W  No Load Power Consumption 500mW (Max)  Polarization - Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 60°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $150W$ No Load Power Consumption $500mW$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorPower DIN, 4 PinSize / Dimension $6.69$ " L x $3.35$ " W x $1.73$ " H (170.0mm x $85.0$ mm x $44.0$ mm)	Voltage - Output	24V
No Load Power Consumption 500mW (Max)  Polarization - ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}$ C $\sim 60^{\circ}$ C  Output Connector Power DIN, 4 Pin  Size / Dimension $6.69^{\circ}$ L x $3.35^{\circ}$ W x $1.73^{\circ}$ H (170.0mm x $85.0$ mm x $44.0$ mm)	Current - Output (Max)	6.25A
Polarization - Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ} \text{W} \times 1.73^{\circ} \text{H} (170.0 \text{mm} \times 85.0 \text{mm} \times 44.0 \text{mm})$	Power (Watts)	150W
Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}$ C $\sim 60^{\circ}$ C  Output Connector Power DIN, 4 Pin  Size / Dimension $6.69^{\circ}$ L x $3.35^{\circ}$ W x $1.73^{\circ}$ H (170.0mm x $85.0$ mm x $44.0$ mm)	No Load Power Consumption	500mW (Max)
Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension $6.69^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0\text{mm x } 85.0\text{mm x } 44.0\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $6.69^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0\text{mm x } 85.0\text{mm x } 44.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Efficiency	Level VI
Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)
		Report errors?

#### ETSA240625U-P51-WP Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ETSA240625U-P51-WP Payment Methods



















## ETSA240625U-P51-WP Shipping Methods













If you have any question about ETSA240625U-P51-WP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com