

EVK105CH2R4JW-F

EVK105CH2R4JW-F Information



For Reference Only

Part Number EVK105CH2R4JW-F

Manufacturer Taiyo Yuden Category Capacitors

Ceramic Capacitors

Description CAP CER 2.4PF 16V C0H 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EVK105CH2R4JW-F Specifications

Manufacturer Part Number EVK105CH2R4JW-F Manufacturer Taiyo Yuden Category Capacitors Package 0402 (1005 Metric) Series EVK Capacitance 2.4pF Tolerance ±5% Voltage - Rated 16V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -		
Category Capacitors Package 0402 (1005 Metric) Series EVK Capacitance 2.4pF Tolerance ±5% Voltage - Rated 16V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Manufacturer Part Number	EVK105CH2R4JW-F
Package 0402 (1005 Metric) Series EVK Capacitance 2.4pF Tolerance ±5% Voltage - Rated 16V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Manufacturer	Taiyo Yuden
Package 0402 (1005 Metric) Series EVK Capacitance 2.4pF Tolerance ±5% Voltage - Rated 16V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Category	Capacitors
Series EVK Capacitance 2.4pF Tolerance ±5% Voltage - Rated 16V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -		Ceramic Capacitors
Capacitance2.4pFTolerance±5%Voltage - Rated16VTemperature CoefficientC0HOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.020" (0.52mm)Lead Spacing-	Package	0402 (1005 Metric)
Tolerance ±5% Voltage - Rated 16V Temperature Coefficient C0H Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Series	EVK
Voltage - Rated Temperature Coefficient COH Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing 16V COH COH COH COH COH COH COH CO	Capacitance	2.4pF
Temperature CoefficientC0HOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.020" (0.52mm)Lead Spacing-	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.020" (0.52mm)Lead Spacing-	Voltage - Rated	16V
FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.020" (0.52mm)Lead Spacing-	Temperature Coefficient	СОН
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Applications	RF, Microwave, High Frequency
Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.020" (0.52mm) -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.020" (0.52mm) Lead Spacing -	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.020" (0.52mm)
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

EVK105CH2R4JW-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EVK105CH2R4JW-F Payment Methods



















EVK105CH2R4JW-F Shipping Methods













If you have any question about EVK105CH2R4JW-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com