



# **EVQ-PLMA15 Information**

For Reference Only

Part Number EVQ-PLMA15

Manufacturer Panasonic Electronic Components

**Category** Switches

**Tactile Switches** 

**Description** SWITCH TACTILE SPST-NO 0.02A 15V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EVQ-PLMA15 Specifications**

Manufacturer Part Number         EVQ-PLMA15           Manufacturer         Panasonic Electronic Components           Category         Switches           Package         -           Series         EVQPL           Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.02A @ 15VDC           Actuator Type         Standard           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         1.50mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         J Lead           Outline         4.90mm x 4.90mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         260gf           Ingress Protection         -           Features         Push Plate		
Category         Switches           Package         -           Series         EVQPL           Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.02A @ 15VDC           Actuator Type         Standard           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         1.50mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         J Lead           Outline         4.90mm x 4.90mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         260gf           Ingress Protection         -           Features         Push Plate	Manufacturer Part Number	EVQ-PLMA15
Package - Series EVQPL Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 15VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.50mm Actuator Length, Right Angle - Top Actuated Termination Style J Lead Outline 4.90mm x 4.90mm Illumination Type, Color - Illumination Type, Color - Colorating Force 260gf Ingress Protection - Coloration	Manufacturer	Panasonic Electronic Components
Package         -           Series         EVQPL           Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.02A @ 15VDC           Actuator Type         Standard           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         1.50mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         J Lead           Outline         4.90mm x 4.90mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         260gf           Ingress Protection         -           Features         Push Plate	Category	Switches
Series         EVQPL           Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.02A @ 15VDC           Actuator Type         Standard           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         1.50mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         J Lead           Outline         4.90mm x 4.90mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         260gf           Ingress Protection         -           Features         Push Plate		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.02A @ 15VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical1.50mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline4.90mm x 4.90mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesPush Plate	Package	-
Switch FunctionOff-MomContact Rating @ Voltage0.02A @ 15VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical1.50mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline4.90mm x 4.90mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesPush Plate	Series	EVQPL
Contact Rating @ Voltage0.02A @ 15VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical1.50mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline4.90mm x 4.90mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesPush Plate	Circuit	SPST-NO
Actuator Type  Mounting Type  Surface Mount  Actuator Height off PCB, Vertical  Actuator Length, Right Angle  - Actuator Orientation  Top Actuated  Termination Style  J Lead  Outline  4.90mm x 4.90mm  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force  260gf  Ingress Protection  Features  Standard  Standard  Standard  Standard  Standard  Surface Mount  1.50mm  Actuator Mount  1.50mm  Top Actuated  -  Non-Actuated  -  -  -  -  -  -  -  -  -  -  -  -  -	Switch Function	Off-Mom
Mounting Type  Actuator Height off PCB, Vertical  Actuator Length, Right Angle  Actuator Orientation  Top Actuated  Termination Style  J Lead  Outline  4.90mm x 4.90mm  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force  260gf  Ingress Protection  Features  Surface Mount  1.50mm  Actuator Mount  Actuator Mount  1.50mm  Actuator Mount  Actuator Mount  1.50mm  Actuator Mount  Actuato	Contact Rating @ Voltage	0.02A @ 15VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.90mm x 4.90mm Illumination Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features  1.50mm 1.5	Actuator Type	Standard
Actuator Length, Right Angle  Actuator Orientation  Top Actuated  Termination Style  J Lead  Outline  4.90mm x 4.90mm  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Operating Force  Ingress Protection  Features  Push Plate	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style J Lead Outline 4.90mm x 4.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Push Plate	Actuator Height off PCB, Vertical	1.50mm
Termination Style J Lead Outline 4.90mm x 4.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Push Plate	Actuator Length, Right Angle	-
Outline 4.90mm x 4.90mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Operating Force 260gf  Ingress Protection -  Features Push Plate	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesPush Plate	Termination Style	J Lead
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesPush Plate	Outline	4.90mm x 4.90mm
Illumination Voltage (Nominal)  Operating Force 260gf  Ingress Protection - Features Push Plate	Illumination	Non-Illuminated
Operating Force 260gf Ingress Protection - Features Push Plate	Illumination Type, Color	-
Ingress Protection Features Push Plate	Illumination Voltage (Nominal)	-
Features Push Plate	Operating Force	260gf
	Ingress Protection	-
Report errors?	Features	Push Plate
		Report errors?

## **EVQ-PLMA15 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EVQ-PLMA15 Payment Methods**





















### **EVQ-PLMA15 Shipping Methods**













If you have any question about EVQ-PLMA15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com