



EVQ-PR3A10 Information



For Reference Only

Part Number EVQ-PR3A10

Manufacturer Panasonic Electronic Components

Category Switches

Tactile Switches

Description SWITCH TACTILE SPDT 0.02A 15V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EVQ-PR3A10 Specifications

Manufacturer Part Number EVQ-PR3A10 Manufacturer Panasonic Electronic Components Category Switches Tactile Switches Package - Series EVQPR Circuit SPDT Switch Function Off-Mom-Mom Conact Rating @ Voltage 0.02A @ 15VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.95mm Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate		
CategorySwitchesPackage-SeriesEVQPRCircuitSPDTSwitch FunctionOff-Mom-MomContact Rating @ Voltage0.02A @ 15VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical0.95mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline6.00mm x 6.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force70/260gfIngress Protection-FeaturesPush Plate	Manufacturer Part Number	EVQ-PR3A10
Package - Series EVQPR Circuit SPDT Switch Function Off-Mom-Mom Contact Rating @ Voltage 0.02A @ 15VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.95mm Actuator Length, Right Angle - Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Type, Color - Illumination Type, Color - Tolorentation - Top Actuated Illumination Voltage (Nominal) - Top Actuated Ingress Protection - Push Plate	Manufacturer	Panasonic Electronic Components
Package - Series EVQPR Circuit SPDT Switch Function Off-Mom-Mom Contact Rating @ Voltage 0.02A @ 15VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.95mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate	Category	Switches
Series EVQPR Circuit SPDT Switch Function Off-Mom-Mom Contact Rating @ Voltage 0.02A @ 15VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.95mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate		Tactile Switches
CircuitSPDTSwitch FunctionOff-Mom-MomContact Rating @ Voltage0.02A @ 15VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical0.95mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline6.00mm x 6.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force70/260gfIngress Protection-FeaturesPush Plate	Package	-
Switch Function Off-Mom-Mom Contact Rating @ Voltage 0.02A @ 15VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.95mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate	Series	EVQPR
Contact Rating @ Voltage 0.02A @ 15VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.95mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate	Circuit	SPDT
Actuator Type Surface Mount Actuator Height off PCB, Vertical 0.95mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate	Switch Function	Off-Mom-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Top Actuated - - - - - - - - - - - - -	Contact Rating @ Voltage	0.02A @ 15VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.95mm 0.95mm 0.95mm - Actuator Operation For Actuated Features 0.95mm 0.95mm - Actuator Operation For Actuated For Actuated	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 70/260gf Ingress Protection Features Push Plate	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate	Actuator Height off PCB, Vertical	0.95mm
Termination Style J Lead Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate	Actuator Length, Right Angle	-
Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 70/260gf Ingress Protection - Features Push Plate	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force70/260gfIngress Protection-FeaturesPush Plate	Termination Style	J Lead
Illumination Type, Color - Illumination Voltage (Nominal) - Coperating Force 70/260gf Ingress Protection - Features Push Plate	Outline	6.00mm x 6.00mm
Illumination Voltage (Nominal)-Operating Force70/260gfIngress Protection-FeaturesPush Plate	Illumination	Non-Illuminated
Operating Force 70/260gf Ingress Protection - Features Push Plate	Illumination Type, Color	-
Ingress Protection Features Push Plate	Illumination Voltage (Nominal)	-
Features Push Plate	Operating Force	70/260gf
	Ingress Protection	-
Report errors?	Features	Push Plate
		Report errors?

EVQ-PR3A10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EVQ-PR3A10 Payment Methods



















EVQ-PR3A10 Shipping Methods













If you have any question about EVQ-PR3A10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com