

## **EVS36-8R4 Information**

Part Number EVS36-8R4

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 36V 300W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EVS36-8R4 Specifications**

Manufacturer Part Number         EVS36-8R4           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         EVS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.4A           Power (Watts)         300W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         91%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         EVS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.4A           Power (Watts)         300W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         91%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Manufacturer Part Number	EVS36-8R4
Package         -           Series         EVS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.4A           Power (Watts)         300W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         91%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package         -           Series         EVS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.4A           Power (Watts)         300W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         91%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         EVS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.4A           Power (Watts)         300W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         91%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.4A           Power (Watts)         300W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         91%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Package	-
Number of Outputs       1         Voltage - Input       85 ~ 265 VAC         Voltage - Output 1       36V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       8.4A         Power (Watts)       300W         Applications       ITE (Commercial)         Voltage - Isolation       3kV (3000V)         Efficiency       91%         Operating Temperature       -20°C ~ 70°C (With Derating)         Features       Adjustable Output, DC Input Capable, PFC, Universal Input         Mounting Type       Chassis Mount         Size / Dimension       7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Series	EVS
Voltage - Input85 ~ 265 VACVoltage - Output 136VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8.4APower (Watts)300WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency91%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Туре	Enclosed
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  Site / Operating Temperature  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Size / Dimension  36V  36V  36V  36V  40  Current - Output (Max)  8.4A  - Current - Output (Max)  8.4A  90W  1TE (Commercial)  30W  40  30W  40  50V  50V  50V  60V  60V  60V  60V  60	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Size / Dimension  Current - Output 4  Current - Output (Max)  8.4A  8.4A  8.4A  8.4A  90W  80W  81TE (Commercial)  8kV (3000V)  91%  Fellorety  91%  Chassis Mount  7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  8.4A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  91%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Voltage - Output 1	36V
Voltage - Output 4  Current - Output (Max)  8.4A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  91%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Voltage - Output 2	-
Current - Output (Max)  8.4A  Power (Watts)  300W  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  91%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  91%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 91%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Current - Output (Max)	8.4A
Voltage - Isolation 3kV (3000V)  Efficiency 91%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Power (Watts)	300W
Efficiency 91%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Applications	ITE (Commercial)
Operating Temperature  -20°C ~ 70°C (With Derating)  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Efficiency	91%
Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm)
		Report errors?

#### **EVS36-8R4 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EVS36-8R4 Payment Methods**



















## **EVS36-8R4 Shipping Methods**













If you have any question about EVS36-8R4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com