

EVS57-5R3 Information

Part Number EVS57-5R3

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 57V 300W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EVS57-5R3 Specifications

| Manufacturer Part Number EVS57-5R3 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) Rockage - Series EVS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 57V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Peatures Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | | |
|--|--------------------------|---|
| Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series EVS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 57V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Manufacturer Part Number | EVS57-5R3 |
| Package - Series EVS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 57V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Manufacturer | TDK-Lambda Americas Inc. |
| Package - Series EVS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 57V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Category | Power Supplies - External/Internal (Off-Board) |
| Series EVS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 57V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | | AC DC Converters |
| Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 57V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Package | - |
| Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 57V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Series | EVS |
| Voltage - Input 85 ~ 265 VAC Voltage - Output 1 57V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Type | Enclosed |
| Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications Voltage - Isolation Size / Dimension 57V 57V 57V 57V 57V 57V 57V 57 | Number of Outputs | 1 |
| Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Voltage - Input | 85 ~ 265 VAC |
| Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Some (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension Size / Dimension - Output (Max) - Current - Output (Max) Some (Watts) S | Voltage - Output 1 | 57V |
| Voltage - Output 4 Current - Output (Max) 5.3A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Voltage - Output 2 | - |
| Current - Output (Max) 5.3A Power (Watts) 300W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Voltage - Output 3 | - |
| Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Voltage - Output 4 | - |
| $ \begin{array}{llllllllllllllllllllllllllllllllllll$ | Current - Output (Max) | 5.3A |
| Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Power (Watts) | 300W |
| Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Applications | ITE (Commercial) |
| Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Voltage - Isolation | 3kV (3000V) |
| Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Efficiency | 90% |
| Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Operating Temperature | -20°C ~ 70°C (With Derating) |
| Size / Dimension 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) | Features | Adjustable Output, DC Input Capable, PFC, Universal Input |
| | Mounting Type | Chassis Mount |
| Report errors? | Size / Dimension | 7.09" L x 3.31" W x 1.54" H (180.0mm x 84.0mm x 39.0mm) |
| | | Report errors? |

EVS57-5R3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EVS57-5R3 Payment Methods



















EVS57-5R3 Shipping Methods













If you have any question about EVS57-5R3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com