

EW-23-09-G-S-260

EW-23-09-G-S-260 Information

Heisener.com	Part Number Manufacturer Category Description Package	EW-23-09-G-S-260 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) .025" BOARD SPACERS	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EW-23-09-G-S-260 Specifications

Manufacturer Part NumberEW-23-09-G-S-260ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, EWNumber of Positions23Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.730" (18.54mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldColorBlack		
CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, EWNumber of Positions23Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.730" (18.54mm)Length - Post (Mating)0.140" (3.55mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Ioµin (0.25µm)Logtact Finish Thickness - Post (Mating)Ioµin (0.25µm)	Manufacturer Part Number	EW-23-09-G-S-260
Number of PositionsCastack, EWNumber of Positions23Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.730" (18.54mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)0.90Ionatt - Finish Thickness - Post (Mating)10µin (0.25µm)	Manufacturer	Samtec Inc.
Package-SeriesFlex Stack, EWNumber of Positions23Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.730" (18.54mm)Length - Post (Mating)0.140" (3.55mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)10µin (0.25µm)	Category	Connectors, Interconnects
SeriesFlex Stack, EWNumber of Positions23Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.730" (18.54mm)Length - Post (Mating)0.140" (3.55mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)10µin (0.25µm)		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions23Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.730" (18.54mm)Length - Post (Mating)0.140" (3.55mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)0.40Juni (0.25µm)10µin (0.25µm)	Package	-
Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.730" (18.54mm)Length - Post (Mating)0.140" (3.55mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)1µin (0.25µm)	Series	Flex Stack, EW
Number of Rows1Row Spacing-Length - Overall0.730" (18.54mm)Length - Post (Mating)0.140" (3.55mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Number of Positions	23
Row Spacing-Length - Overall0.730" (18.54mm)Length - Post (Mating)0.140" (3.55mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldLongth - Finish Thickness - Post (Mating)10µin (0.25µm)	Pitch	0.100" (2.54mm)
Length - Overall0.730" (18.54mm)Length - Post (Mating)0.140" (3.55mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Number of Rows	1
Length - Post (Mating)0.140" (3.55mm)Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Row Spacing	-
Length - Stack Height0.260" (6.60mm)Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Length - Overall	0.730" (18.54mm)
Length - Tail0.330" (8.38mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Length - Post (Mating)	0.140" (3.55mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Length - Stack Height	0.260" (6.60mm)
TerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Length - Tail	0.330" (8.38mm)
Contact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 10µin (0.25µm)	Termination	Solder
	Contact Finish - Post (Mating)	Gold
Color Black	Contact Finish Thickness - Post (Mating)	10µin (0.25µm)
	Color	Black
Report e		Report errors?

EW-23-09-G-S-260 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EW-23-09-G-S-260 Payment Methods



EW-23-09-G-S-260 Shipping Methods



If you have any question about EW-23-09-G-S-260, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com