



### **EXA.1B.308.HLN Information**

Heisener.com

Part Number EXA.1B.308.HLN

Manufacturer LEMO

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PNL MNT RCPT 8SKT R/A PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EXA.1B.308.HLN Specifications**

| Manufacturer Part Number       EXA.IB.308.HLN         Manufacturer       LEMO         Category       Connectors, Interconnects         Package       -         Series       IB         Connector Type       Receptacle, Female Sockets         Number of Positions       8         Shell Size - Insert       308         Shell Size, MIL       -         Mounting Type       Panel Mount, Bulkhead; Through Hole, Right Angle         Termination       Solder         Fastening Type       Push-Pull, Detent Lock         Orientation       A         Ingress Protection       IP50 - Dust Protected         Shell Material, Finish       Polyphenylene Sulfide (PPS)         Contact Finish       Gold         Features       Shielded         Voltage - Rated       -         Current Rating       5A |                          |  |
|--|--------------------------|--|
| CategoryConnectors, InterconnectsPackage-Series1BConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationAIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A  | Manufacturer Part Number | EXA.1B.308.HLN                                   |
| Package-Series1BConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationAIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A   | Manufacturer             | LEMO   |
| Package-Series1BConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationAIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A   | Category                 | Connectors, Interconnects                        |
| Series1BConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationAIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A   |                          | Circular Connectors                              |
| Connector Type Receptacle, Female Sockets  Number of Positions 8  Shell Size - Insert 308  Shell Size, MIL -  Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle  Termination Solder  Fastening Type Push-Pull, Detent Lock  Orientation A  Ingress Protection IP50 - Dust Protected  Shell Material, Finish Polyphenylene Sulfide (PPS)  Contact Finish Gold  Features Shielded  Voltage - Rated -  Current Rating 5A   | Package                  | -  |
| Number of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationAIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A   | Series                   | 1B   |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation A Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A  | Connector Type           | Receptacle, Female Sockets                       |
| Shell Size, MIL  Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle  Termination Solder  Fastening Type Push-Pull, Detent Lock  Orientation A  Ingress Protection IP50 - Dust Protected  Shell Material, Finish Polyphenylene Sulfide (PPS)  Contact Finish Gold  Features Shielded  Voltage - Rated -  Current Rating 5A  | Number of Positions      | 8  |
| Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationAIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5A   | Shell Size - Insert      | 308  |
| Termination Solder Fastening Type Push-Pull, Detent Lock Orientation A Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A   | Shell Size, MIL          | -  |
| Fastening Type Push-Pull, Detent Lock Orientation A Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A  | Mounting Type            | Panel Mount, Bulkhead; Through Hole, Right Angle |
| Orientation A Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A  | Termination              | Solder   |
| Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5A  | Fastening Type           | Push-Pull, Detent Lock                           |
| Shell Material, Finish Polyphenylene Sulfide (PPS)  Contact Finish Gold  Features Shielded  Voltage - Rated - Current Rating 5A  | Orientation              | A  |
| Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 5A   | Ingress Protection       | IP50 - Dust Protected                            |
| Features Shielded  Voltage - Rated - Current Rating 5A   | Shell Material, Finish   | Polyphenylene Sulfide (PPS)                      |
| Voltage - Rated - Current Rating 5A  | Contact Finish           | Gold   |
| Current Rating 5A  | Features                 | Shielded   |
|  | Voltage - Rated          | -  |
| Report errors?   | Current Rating           | 5A   |
|  |                          | Report errors?                                   |

#### **EXA.1B.308.HLN Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EXA.1B.308.HLN Payment Methods**



















## **EXA.1B.308.HLN Shipping Methods**













If you have any question about EXA.1B.308.HLN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com