

EXB30-48S2V5 Information

Heisener.com

Part Number EXB30-48S2V5

ManufacturerArtesyn Embedded TechnologiesCategoryPower Supplies - Board Mount

DC DC Converters

Description CONV DC/DC OPEN FRM 2.5V OUT 30W

Package 9-DIP Module, 8 Leads

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EXB30-48S2V5 Specifications

Manufacturer Category Power Supplies - Board Mount DC DC Converters Package 9-DIP Module, 8 Leads Series EXB30 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) Voltage - Output 1 2.5V Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation 1.5kV (1500V) Applications Features Artesyn Embedded Technologies Power Supplies - Board Mount 2.5D Power Supplies - Board Mount 1 Artesyn Embedded Technologies Power Supplies - Board Mount 2.5D Power Supplies - Board Mount 1 2.5V Voltage - Input (Max) Power (Watts) Power (Watts) Power (Watts) Power (Watts) Power (Orp. OTP, OVP, SCP, UVLO)		
Category Power Supplies - Board Mount DC DC Converters Package 9-DIP Module, 8 Leads Series EXB30 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 75V Voltage - Output 1 2.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Manufacturer Part Number	EXB30-48S2V5
DC DC Converters Package 9-DIP Module, 8 Leads Series EXB30 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 75V Voltage - Output 1 2.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Manufacturer	Artesyn Embedded Technologies
Package 9-DIP Module, 8 Leads Series EXB30 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 75V Voltage - Output 1 2.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Category	Power Supplies - Board Mount
Series EXB30 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 75V Voltage - Output 1 2.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 75V Voltage - Output 1 2.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Package	9-DIP Module, 8 Leads
Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 75V Voltage - Output 1 2.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Series	EXB30
Voltage - Input (Min) 36V Voltage - Input (Max) 75V Voltage - Output 1 2.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Type	Isolated Module
Voltage - Input (Max) 75V Voltage - Output 1 2.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Number of Outputs	1
Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Voltage - Input (Min)	36V
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Voltage - Input (Max)	75V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Voltage - Output 1	2.5V
Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Voltage - Output 2	-
Current - Output (Max) 8A Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Voltage - Output 3	-
Power (Watts) 20W Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Voltage - Output 4	-
Voltage - Isolation 1.5kV (1500V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Current - Output (Max)	8A
Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Power (Watts)	20W
Features Remote On/Off, OCP, OTP, OVP, SCP, UVLO	Voltage - Isolation	1.5kV (1500V)
	Applications	ITE (Commercial)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Features	Remote On/Off, OCP, OTP, OVP, SCP, UVLO
	Operating Temperature	-40°C ~ 85°C
Efficiency 87%	Efficiency	87%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case 9-DIP Module, 8 Leads	Package / Case	9-DIP Module, 8 Leads
Size / Dimension 2.40" L x 2.28" W x 0.43" H (61.0mm x 57.9mm x 10.9mm)	Size / Dimension	2.40" L x 2.28" W x 0.43" H (61.0mm x 57.9mm x 10.9mm)

Supplier Device Package	-
Control Features	Enable, Active High
	Report errors?

EXB30-48S2V5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EXB30-48S2V5 Payment Methods



















EXB30-48S2V5 Shipping Methods













If you have any question about EXB30-48S2V5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com