



EXR2N902RTN Information

Heisener.com

Part Number EXR2N902RTN

Manufacturer Laird Technologies IAS

Category RF/IF and RFID

RF Antennas

Description ANT TUF DUCK 902-928MHZ

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EXR2N902RTN Specifications

Manufacturer Part Number EXR2N902RTN Manufacturer Laird Technologies IAS Category RF/IF and RFID RF Antennas RFAntennas Package - Series EXR Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 915MHz Frequency Range 902MHz ~ 928MHz Antenna Type Whip, Straight Number of Bands 1 VSWR - Return Loss - Gain - Power - Max - Features - Termination Connector Ingress Protection - Mounting Type Connector Mount Height (Max) - Applications -	*	
Category RF/IF and RFID RF Antennas RF Antennas Package - Series EXR Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 915MHz Frequency Range 902MHz ~ 928MHz Antenna Type Whip, Straight Number of Bands 1 VSWR - Return Loss - Gain - Power - Max - Features - Termination Connector Ingress Protection - Mounting Type Connector Mount Height (Max) - Applications -	Manufacturer Part Number	EXR2N902RTN
Package - Series EXR Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 915MHz Frequency Range 902MHz ~ 928MHz Antenna Type Whip, Straight Number of Bands 1 VSWR - Return Loss - Gain - Power - Max - Features - Termination Connector Ingress Protection - Mounting Type Connector Mount Height (Max) - Applications -	Manufacturer	Laird Technologies IAS
Package - Series EXR Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 915MHz Frequency Range 902MHz ~ 928MHz Antenna Type Whip, Straight Number of Bands 1 VSWR - Return Loss - Gain - Power - Max - Features - Termination Connector Ingress Protection - Mounting Type Connector Mount Height (Max) - Applications -	Category	RF/IF and RFID
Series EXR Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 915MHz Frequency Range 902MHz ~ 928MHz Antenna Type Whip, Straight Number of Bands 1 VSWR - Return Loss - Gain - Power - Max - Features - Termination Connector Ingress Protection - Mounting Type Connector Mount Height (Max) - Applications -		RF Antennas
Frequency Group Frequency (Center/Band) Frequency Range 902MHz ~ 928MHz Antenna Type Whip, Straight Number of Bands 1 VSWR - Return Loss Gain - Power - Max Features - Termination Ingress Protection Mounting Type Connector Mount Height (Max) Applications UHF (300 MHz ~ 1 GHz) 915MHz 915MHz 928MHz Whip, Straight	Package	-
Frequency (Center/Band) Frequency Range 902MHz ~ 928MHz Antenna Type Whip, Straight 1 VSWR - Return Loss - Gain Power - Max Features - Termination Ingress Protection Mounting Type Mounting Type Height (Max) Applications 902MHz ~ 928MHz Whip, Straight 1 - Connector Connector Connector Connector Mount - Connector Mount - Connector Mount - Connector Mount - Connector Mount	Series	EXR
Frequency Range 902MHz ~ 928MHz Antenna Type Whip, Straight Number of Bands 1 VSWR	Frequency Group	UHF (300 MHz ~ 1 GHz)
Antenna Type Whip, Straight Number of Bands 1 VSWR Return Loss Gain Power - Max Features Termination Connector Ingress Protection Mounting Type Connector Mount Height (Max) Applications Applications Whip, Straight Connector Connector Whip, Straight Connector Connector Connector Connector Mount Connector Mount Connector Mount	Frequency (Center/Band)	915MHz
Number of Bands 1 VSWR - Return Loss - Gain - Power - Max - Features - Termination Connector Ingress Protection - Mounting Type Connector Mount Height (Max) - Applications -	Frequency Range	902MHz ~ 928MHz
VSWR Return Loss - Gain - Power - Max - Features - Termination Ingress Protection Mounting Type Connector Mount Height (Max) Applications - Connector - Applications - Connector Mount - Connect	Antenna Type	Whip, Straight
Return Loss - Gain	Number of Bands	1
Gain-Power - Max-Features-TerminationConnectorIngress Protection-Mounting TypeConnector MountHeight (Max)-Applications-	VSWR	-
Power - Max	Return Loss	-
Features - Connector Ingress Protection - Connector Mounting Type Connector Mount Height (Max) - Applications - Connector Mount - Connecto	Gain	-
Termination Connector Ingress Protection - Mounting Type Connector Mount Height (Max) - Applications -	Power - Max	-
Ingress Protection - Mounting Type Connector Mount Height (Max) - Applications -	Features	-
Mounting Type Connector Mount Height (Max) - Applications - Connector Mount	Termination	Connector
Height (Max) - Applications -	Ingress Protection	-
Applications -	Mounting Type	Connector Mount
	Height (Max)	-
Report errors?	Applications	-
Report errors.		Report errors?

EXR2N902RTN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EXR2N902RTN Payment Methods



















EXR2N902RTN Shipping Methods













If you have any question about EXR2N902RTN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com