



# **EXSN2400RSM Information**

Heisener.com

Part Number EXSN2400RSM

Manufacturer Laird Technologies IAS

Category RF/IF and RFID

**RF** Antennas

**Description** ANT TUF DUCK VHF 2.4GHZ

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **EXSN2400RSM Specifications**

Manufacturer Part Number         EXSN2400RSM           Manufacturer         Laird Technologies IAS           Category         RF/IF and RFID           RFAntennas         RFAntennas           Package         -           Series         EXS           Frequency Group         UHF (2 GHz ~ 3 GHz)           Frequency (Center/Band)         2.4GHz           Frequency Range         -           Antenna Type         Whip, Straight           Number of Bands         1           VSWR         -           Return Loss         -           Gain         -           Power - Max         -           Features         -           Termination         Connector, RP-SMA Male           Ingress Protection         -           Mounting Type         Connector Mount           Height (Max)         4.000" (101.60mm)           Applications         -		
Category         RF/IF and RFID           RF Antennas           Package         -           Series         EXS           Frequency Group         UHF (2 GHz ~ 3 GHz)           Frequency (Center/Band)         2.4GHz           Frequency Range         -           Antenna Type         Whip, Straight           Number of Bands         1           VSWR         -           Return Loss         -           Gain         -           Power - Max         -           Features         -           Termination         Connector, RP-SMA Male           Ingress Protection         -           Mounting Type         Connector Mount           Height (Max)         4.000" (101.60mm)           Applications         -	Manufacturer Part Number	EXSN2400RSM
Package         -           Series         EXS           Frequency Group         UHF (2 GHz ~ 3 GHz)           Frequency (Center/Band)         2.4GHz           Frequency Range         -           Antenna Type         Whip, Straight           Number of Bands         1           VSWR         -           Return Loss         -           Gain         -           Power - Max         -           Features         -           Termination         Connector, RP-SMA Male           Ingress Protection         -           Mounting Type         Connector Mount           Height (Max)         4.000" (101.60mm)           Applications         -	Manufacturer	Laird Technologies IAS
Package         -           Series         EXS           Frequency Group         UHF (2 GHz ~ 3 GHz)           Frequency (Center/Band)         2.4 GHz           Frequency Range         -           Antenna Type         Whip, Straight           Number of Bands         1           VSWR         -           Return Loss         -           Gain         -           Power - Max         -           Features         -           Termination         Connector, RP-SMA Male           Ingress Protection         -           Mounting Type         Connector Mount           Height (Max)         4.000" (101.60mm)           Applications         -	Category	RF/IF and RFID
SeriesEXSFrequency GroupUHF (2 GHz ~ 3 GHz)Frequency (Center/Band)2.4GHzFrequency Range-Antenna TypeWhip, StraightNumber of Bands1VSWR-Return Loss-Gain-Power - Max-Features-TerminationConnector, RP-SMA MaleIngress Protection-Mounting TypeConnector MountHeight (Max)4.000" (101.60mm)Applications-		RF Antennas
Frequency Group Frequency (Center/Band) Frequency Range - Antenna Type Whip, Straight Number of Bands 1 VSWR - Return Loss Gain - Power - Max Features - Termination Ingress Protection Mounting Type Height (Max) Applications  UHF (2 GHz ~ 3 GHz) 2.4GHz 3 GHz) 2.4GHz 4.GHz 4.GH	Package	-
Frequency (Center/Band)  Frequency Range  Antenna Type  Whip, Straight  Number of Bands  1  VSWR  - Return Loss  - Gain  Power - Max  Features  Termination  Ingress Protection  Mounting Type  Height (Max)  Applications  -  2.4GHz  Whip, Straight  Aphlications  1  Connector Mount  Connector Mount  4.000" (101.60mm)  -  Applications	Series	EXS
Frequency Range - Miniparty - Whip, Straight - Whip, Straight - St	Frequency Group	UHF (2 GHz ~ 3 GHz)
Antenna TypeWhip, StraightNumber of Bands1VSWR-Return Loss-Gain-Power - Max-Features-TerminationConnector, RP-SMA MaleIngress Protection-Mounting TypeConnector MountHeight (Max)4.000" (101.60mm)Applications-	Frequency (Center/Band)	2.4GHz
Number of Bands1VSWR-Return Loss-Gain-Power - Max-Features-TerminationConnector, RP-SMA MaleIngress Protection-Mounting TypeConnector MountHeight (Max)4.000" (101.60mm)Applications-	Frequency Range	-
VSWR Return Loss - Gain - Power - Max - Features - Termination Ingress Protection Mounting Type Height (Max) Applications - Connector Mount 4.000" (101.60mm) - Connector Mount - Connector Moun	Antenna Type	Whip, Straight
Return Loss Gain - Power - Max - Features - Termination Ingress Protection Mounting Type Connector Mount Height (Max) Applications - Connector Mount 4.000" (101.60mm) - Connector Mount - Conne	Number of Bands	1
Gain  Power - Max  - Features  - Termination  Connector, RP-SMA Male  Ingress Protection  Mounting Type  Connector Mount  Height (Max)  Applications  -  Connector Mount  4.000" (101.60mm)  -  Connector Mount	VSWR	-
Power - Max - Canal - Features - Connector, RP-SMA Male Connector Mounting Type Connector Mount Height (Max) 4.000" (101.60mm) Applications - Canal Ca	Return Loss	-
Features - Connector, RP-SMA Male Ingress Protection - Connector Mount Mounting Type Connector Mount Height (Max) 4.000" (101.60mm) Applications -	Gain	-
Termination Connector, RP-SMA Male Ingress Protection - Mounting Type Connector Mount Height (Max) 4.000" (101.60mm) Applications -	Power - Max	-
Ingress Protection - Connector Mount  Mounting Type Connector Mount  Height (Max) 4.000" (101.60mm)  Applications -	Features	-
Mounting TypeConnector MountHeight (Max)4.000" (101.60mm)Applications-	Termination	Connector, RP-SMA Male
Height (Max)       4.000" (101.60mm)         Applications       -	Ingress Protection	-
Applications -	Mounting Type	Connector Mount
	Height (Max)	4.000" (101.60mm)
Report errors?	Applications	-
		Report errors?

#### **EXSN2400RSM Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EXSN2400RSM Payment Methods**



















### **EXSN2400RSM Shipping Methods**













If you have any question about EXSN2400RSM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com