

EXV337M016A9MAA

EXV337M016A9MAA Information



For Reference Only

Part Number	EXV337M016A9MAA	
Manufacturer	KEMET	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	ALU ELECTROLYTIC SMD EXV 16VDC 8	
Package	Radial, Can - SMD	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EXV337M016A9MAA Specifications

Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesEXVCapacitance30µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Deraring Temperature5000 Hrs @ 105°COperating Temperature50°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - High Frequency600mA @ 100kHzImpedance160 mOhmsLied Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" Dia (8.00mm x 8.30mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Pokage / CaseSatial, Can - SMD	Manufacturer Part Number	EXV337M016A9MAA
Adminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesEXVCapacitance330µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency420mA @ 120HzRipple Current - High Frequency600mA @ 100kHzImpedance.Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Package / CaseRadial, Can - SMD	Manufacturer	KEMET
PackageRadial, Can - SMDSeriesEXVCapacitance330µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarization-55°C ~ 105°CApplicationsAudioRipple Current - Low Frequency420mA @ 120HzRipple Current - High Frequency600mA @ 100kHzImpedance-Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Package / CaseRadial, Can - SMD	Category	Capacitors
SeriesEXVCapacitance330µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency420mA @ 120HzInpedance160 mOhmsLiad Spacing-Size / Dimension0.315" Dia (8.00mn)Height - Seated (Max)0.327" L x 0.327" W (8.30mm x 8.30mm)Surface Mount Land SizeSurface MountMounting TypeSurface MountPackage / CaseKadial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency600mA @ 100kHzImpedance160 mOhmsLead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPokage / CaseRadial, Can - SMD	Package	Radial, Can - SMD
Tolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency600mA @ 120HzImpedance160 mOhmsLead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Pokage / CaseRadial, Can - SMD	Series	EXV
Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency420mA @ 120HzBipple Current - High Frequency600mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface Mount Land SizePackage / CaseRatial, Can - SMD	Capacitance	330µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsAudioApple Current - Low Frequency420mA @ 120HzRipple Current - High Frequency600mA @ 100kHzImpedance-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.327" L x 0.327" W (8.30mm x 8.30mm)Surface Mount Land SizeSurface MountMounting TypeReida (Can - SMD)	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency420mA @ 120HzBipple Current - High Frequency600mA @ 100kHzImpedance160 mOhmsLead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeRadial, Can - SMD	Voltage - Rated	16V
Operating Temperature -55°C ~ 105°C Polar Polar Polarization Polar Applications Audio Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency 600mA @ 100kHz Impedance 160 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Package / Case Radial, Can - SMD	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsAudioRipple Current - Low Frequency420mA @ 120HzRipple Current - High Frequency600mA @ 100kHzImpedance160 mOhmsLead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsAudioRipple Current - Low Frequency420mA @ 120HzRipple Current - High Frequency600mA @ 100kHzImpedance160 mOhmsLead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency420mA @ 120HzRipple Current - High Frequency600mA @ 100kHzImpedance160 mOhmsLead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency 600mA @ 100kHz Impedance 160 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Applications	Audio
Impedance160 mOhmsLead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - Low Frequency	420mA @ 120Hz
Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - High Frequency	600mA @ 100kHz
Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Impedance	160 mOhms
Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lead Spacing	-
Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Height - Seated (Max)	0.413" (10.50mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.327" L x 0.327" W (8.30mm x 8.30mm)
-	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report errors?

EXV337M016A9MAA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EXV337M016A9MAA Payment Methods



If you have any question about EXV337M016A9MAA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com