

# EZC15DRTH

a Quote

## **EZC15DRTH Information**

		Part Number	EZC15DRTH	
		Manufacturer	Sullins Connector Solutions	
	When here we want	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	「読む
	The second	Description	CONN EDGE DUAL FMALE 30POS 0.100	나염문
		Package	-	
			For the pricing/inventory/lead time, please contact	
			us	
	For Reference Only		Website: https://www.heisener.com	Request a
			E-mail: salesdept@heisener.com	Request

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **EZC15DRTH Specifications**

Manufacturer Part Number EZC15DRTH   Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects   Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors   Package -   Stries -   Card Fdge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors   Stries -   Card Type -   Gender Non Specified - Dual Edge   Number of Positions/Bay/Row 15   Number of Positions/Bay/Row 30   Number of Positions 0.062° (1.57mm)   Statute 0.00° (2.54mm)   Features -   Mounting Type 1010° (2.54mm)   Young Hole Solder   Torniation Solder   Contact Material Solder   Contact Finish Thickness Gold   Contact Finish Thickness Gold   Contact Finish Thickness Iopin Octstyme   Color Bue   Falage Feature Toy Mount Openining, Unthreaded, 0.125° (3.18mm) Dia	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Nongh HoleSolderContact MaterialSolderContact FinishGoldContact Finish ThicknessIpi (0.25µm)Contact TypeFull BellowsContact TypeSull Sull Sull Sull Sull Sull Sull Sull	Manufacturer Part Number	EZC15DRTH
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type5Contact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeHullellowsContact TypeSolderContact TypeSolderCont	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Sumber of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeMoleContact MaterialSolderContact FinishGoldContact Finish Thickness10uin (0.25µm)Contact TypeHule HolesContact Type10µin (0.25µm)Contact Type10µin (0.25µm)Contact TypeFul BellowsColorBueFaga Feature0.001 (0.25µm) DiaForage Feature56°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIupin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFul BellowsColorBlueFlange FeatureTor Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Series	-
Number of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-Mounting TypeSolderContact MaterialPhosphor BronzeContact Finish Thickness0.004Contact TypeGuldContact TypeFull BellowsColorBueFange Feature-Forge Type Type-Contact Type-Solder-ColorBiteColor-Fange Feature-Contact Type-Contact Finish-Color-Solder-Color-Solder-Color-Solder-Fange Feature-Contact Spec-Contact Spec-Color-Solder-Solder-Solder-Color-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-<	Card Type	Non Specified - Dual Edge
Number of Positions 30   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features -   Mounting Type Through Hole   Contact Material Solder   Contact Finish Gold   Contact Finish Thickness 10µin (0.25µm)   Contact Type Full Bellows   Color Bue   Flange Feature -   Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange FeatureContact OpenationOperating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	15
Number of Rows2Nich0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	30
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C~125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessJuµin (0.25µm)Contact TypeFul BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **EZC15DRTH Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE UARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EZC15DRTH Payment Methods**



# **EZC15DRTH Shipping Methods**



If you have any question about EZC15DRTH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com