

F-196U Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



F-196U Specifications

ManufacturerTriad MagneticsManufacturerTriad MagneticsCategoryTransformersPower TransformersPower TransformersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 15.5V, Series 32VCurrent - Output (Max)SinglePrimary Winding(s)SingleSecondary Winding(s)DualPower - Max63 VA		
CategoryTransformersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 15.5V, Series 32VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - MaxG3 VAMounting TypeChassis MountSize / Dimension71.42mm L x 66.68mm WSize / Dimension55.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Manufacturer Part Number	F-196U
InterfactFormersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 15.5V, Series 32VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - MaxG3 VAMounting TypeChassis MountSize / Dimension71.42mm Lx 66.68mm WSize / Dimension55.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Manufacturer	Triad Magnetics
Package-Series-TypeLaminated CoreVoltage - PrimaryI15VVoltage - Secondary (Full Load)Parallel 15.5V, Series 32VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max63 VAMounting TypeChasis MountTermination StyleNire LeadsSize / Dimension1.42mm L x 66.68mm WHeight - Seated (Max)SicoNrmsWotage - Isolation1.500 rmsWeightMentWeightSicoNrmsStation StyleSicoNrmsStation Style<	Category	Transformers
Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 15.5V, Series 32VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max63 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)55.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)		Power Transformers
TypeLaminated CoreTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 15.5V, Series 32VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - MaxG3 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)S5.73mmWoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Package	-
A115VVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 15.5V, Series 32VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max63 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Series	-
Voltage - Secondary (Full Load)Parallel 15.5V, Series 32VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max63 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Туре	Laminated Core
Current - Output (Max)Parallel 2A, Series 1APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max63 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max63 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Voltage - Secondary (Full Load)	Parallel 15.5V, Series 32V
Secondary Winding(s)DualCenter TapYesPower - Max63 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Current - Output (Max)	Parallel 2A, Series 1A
Center TapYesPower - Max63 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Primary Winding(s)	Single
Power - Max63 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Secondary Winding(s)	Dual
Nounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Center Tap	Yes
Termination StyleWire LeadsSize / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Power - Max	63 VA
Size / Dimension71.42mm L x 66.68mm WHeight - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Mounting Type	Chassis Mount
Height - Seated (Max)85.73mmVoltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Termination Style	Wire Leads
Voltage - Isolation1500VrmsWeight4 lbs (1.8kg)	Size / Dimension	71.42mm L x 66.68mm W
Weight 4 lbs (1.8kg)	Height - Seated (Max)	85.73mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	4 lbs (1.8kg)
		Report errors?

F-196U Guarantees



If you have any question about F-196U, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com