

F-251X Information



For Reference Only

Part Number F-251X

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description POWER XFMR CHASSIS MOUNT W/LEADS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell









F-251X Specifications

Manufacturer Part Number F-251X Manufacturer Triad Magnetics Category Transformers Power Transformers Power Transformers Series Single Secondary Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 14V Current - Output (Max) 2A Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 28 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) 57.15mm Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)		
Category Transformers Package - Series Single Secondary Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 14V Current - Output (Max) 2A Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 28 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) 57.15mm Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)	Manufacturer Part Number	F-251X
Package - Series Single Secondary Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 14V Current - Output (Max) 2A Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 28 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) 57.15mm Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)	Manufacturer	Triad Magnetics
Package - Series Single Secondary Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 14V Current - Output (Max) 2A Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 28 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) 57.15mm Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)	Category	Transformers
SeriesSingle SecondaryTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)14 VCurrent - Output (Max)2APrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max28 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension93.65mm L x 49.0mm WHeight - Seated (Max)57.15mmVoltage - Isolation1500VrmsWeight1.5 lbs (680.4g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 14V Current - Output (Max) 2A Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 28 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) 57.15mm Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max 28 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension Height - Seated (Max) Voltage - Isolation Wind Leads 57.15mm Voltage - Isolation Wind Leads 1.5 lbs (680.4g)	Series	Single Secondary
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max 28 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation 1.5 lbs (680.4g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max 28 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Single Yes Vhes Yes Vas Vas Single Yes Yes Ves Vire Sav VA Single Yes Vas VA Single Yes Vas VA Single Yes Vas VA Single Yes VA Single Yes Single Yes Single Yes Single Yes Single Yes Single Yes Single Single Yes Single Yes Single Single Yes Single Single Yes Single	Voltage - Secondary (Full Load)	14V
Secondary Winding(s)SingleCenter TapYesPower - Max28 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension93.65mm L x 49.0mm WHeight - Seated (Max)57.15mmVoltage - Isolation1500VrmsWeight1.5 lbs (680.4g)	Current - Output (Max)	2A
Center TapYesPower - Max28 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension93.65mm L x 49.0mm WHeight - Seated (Max)57.15mmVoltage - Isolation1500VrmsWeight1.5 lbs (680.4g)	Primary Winding(s)	Single
Power - Max Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) 57.15mm Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)	Secondary Winding(s)	Single
Mounting Type Chassis Mount Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) 57.15mm Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)	Center Tap	Yes
Termination Style Wire Leads Size / Dimension 93.65mm L x 49.0mm W Height - Seated (Max) 57.15mm Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)	Power - Max	28 VA
Size / Dimension93.65mm L x 49.0mm WHeight - Seated (Max)57.15mmVoltage - Isolation1500VrmsWeight1.5 lbs (680.4g)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Veight 57.15mm 1500Vrms 1.5 lbs (680.4g)	Termination Style	Wire Leads
Voltage - Isolation 1500Vrms Weight 1.5 lbs (680.4g)	Size / Dimension	93.65mm L x 49.0mm W
Weight 1.5 lbs (680.4g)	Height - Seated (Max)	57.15mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	1.5 lbs (680.4g)
		Report errors?

F-251X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F-251X Payment Methods





















F-251X Shipping Methods













If you have any question about F-251X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com