

F-270X

F-270X Information



 Part Number
 F-270X

 Manufacturer
 Triad Magnetics

 Category
 Transformers Power Transformers

 Description
 POWER XFMR CHASSIS MOUNT W/LEADS

 Package

 For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



F-270X Specifications

Manufacturer Part Number F-270X Manufacturer Trial Magnetics Category Transformers Package - Series Single Secondary Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 40V Current - Output (Max) IA Primary Winding(s) Single Secondary Winding(s) Single Power - Max 40 VA Mounting Type Yes Power - Max 40 VA Mounting Type Chassis Mount Termination Style Sicondary III Addited Core Size / Dimension 101.60mm L x 57.15mm W Voltage - Isolation 500Vrms		
CategoryTransformersPackage-SeriesSingle SecondaryTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)40VCurrent - Output (Max)IAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max40 VAMounting TypeChasis MountSize / Dimension101.60mm Lx 57.15mm WSize / Dimension50.7mmHeight - Seated (Max)50.07mmWeight150VrmsWeight2.6 lbs (1.2kg)	Manufacturer Part Number	F-270X
Power TransformersPackage-SeriesSingle SecondaryTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)40VCurrent - Output (Max)IAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max40 VAMounting TypeChasis MountSize / Dimension101.60mm Lx 57.15mm WSize / Dimension50.7mmHeight - Seated (Max)500 VrmsWeight2.6 lbs (1.2kg)	Manufacturer	Triad Magnetics
Package-Package-SeriesSingle ScondaryTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)40VCurrent - Output (Max)IAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - MaxOVAMounting TypeChasis MountTermination StyleWire LeadsSize / Dimension10.60mm Lx 57.15mm WHeight - Seated (Max)50.07mmWotage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Category	Transformers
SeriesSingle SecondaryTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)40VCurrent - Output (Max)IAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max40 VAMounting TypeChassis MountTermination StyleUir LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)55.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)		Power Transformers
TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)40VCurrent - Output (Max)IAPrimary Winding(s)SingleSecondary Winding(s)SinglePower - Max40 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)55.07mmWingter1500VrmsWeight2.6 lbs (1.2kg)	Package	-
Yoltage - Primary115VVoltage - Secondary (Full Load)40VCurrent - Output (Max)1APrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max40 VAMounting TypeChassis MountTermination StyleNire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)55.07mmWoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Series	Single Secondary
Voltage - Secondary (Full Load)40VCurrent - Output (Max)1APrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max40 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)65.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Туре	Laminated Core
Current - Output (Max)IAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max40 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)55.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max40 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)55.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Voltage - Secondary (Full Load)	40V
Secondary Winding(s)SingleCenter TapYesPower - Max40 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)65.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Current - Output (Max)	1A
Center TapYesPower - Max40 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)65.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Primary Winding(s)	Single
Power - Max40 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)65.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)65.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Center Tap	Yes
Termination StyleWire LeadsSize / Dimension101.60mm L x 57.15mm WHeight - Seated (Max)65.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Power - Max	40 VA
Size / Dimension 101.60mm L x 57.15mm W Height - Seated (Max) 65.07mm Voltage - Isolation 1500Vrms Weight 2.6 lbs (1.2kg)	Mounting Type	Chassis Mount
Height - Seated (Max)65.07mmVoltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Termination Style	Wire Leads
Voltage - Isolation1500VrmsWeight2.6 lbs (1.2kg)	Size / Dimension	101.60mm L x 57.15mm W
Weight 2.6 lbs (1.2kg)	Height - Seated (Max)	65.07mm
-	Voltage - Isolation	1500Vrms
Report errors?	Weight	2.6 lbs (1.2kg)
		Report errors?

F-270X Guarantees



If you have any question about F-270X, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com