

F-92A Information



For Reference Only

Part Number F-92A

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description POWER XFMR CHASSIS MOUNT W/LEADS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F-92A Specifications

Manufacturer Part Number F-92A Manufacturer Triad Magnetics Category Transformers Package - Series Universal Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 10V, 20V, 40V Current - Output (Max) 750mA Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 76.20mm W Height - Seated (Max) 76.20mm Voltage - Isolation 1500Vrms Weight 3.3 lbs (1.5kg)	-	
Category Power Transformers Package - Series Universal Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 10V, 20V, 40V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Transformers Power Transformers Universal Laminated Core Laminated Core Universal Varies Single, Multiple Taps Varies Varies Mounting Type Chassis Mount Termination Style Size / Dimension 1500Vrms Weight 3.3 lbs (1.5kg)	Manufacturer Part Number	F-92A
Package - Series Universal Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 10V, 20V, 40V Current - Output (Max) 750mA Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 76.20mm W Height - Seated (Max) 76.20mm Voltage - Isolation 1500Vrms Weight 3.3 lbs (1.5kg)	Manufacturer	Triad Magnetics
Package - Universal Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 10 V, 20 V, 40 V Current - Output (Max) 750mA Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 76.20mm W Height - Seated (Max) 76.20mm Voltage - Isolation 1500 Vrms Weight	Category	Transformers
Series Universal Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 10 V, 20 V, 40 V Current - Output (Max) 750 mA Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50 mm L x 76.20 mm W Voltage - Isolation 1500 V rms Weight 3.3 lbs (1.5 kg)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 10V, 20V, 40V Current - Output (Max) 750mA Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 76.20mm W Height - Seated (Max) 76.20mm Voltage - Isolation 1500Vrms Weight 3.3 lbs (1.5kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 115V 11	Series	Universal
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 10V, 20V, 40V 750mA 750mA Single, Multiple Taps No Varies No Varies Wire Leads 63.50mm L x 76.20mm W 1500Vrms 3.3 lbs (1.5kg)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 750mA 750mA 750mA 750mA 750mA 750mA 760m No Varies No Varies No Varies Varies About Varies Varies Wire Leads 63.50mm L x 76.20mm W 76.20mm 76.20mm Voltage - Isolation 1500Vrms 3.3 lbs (1.5kg)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Single, Multiple Taps Secondary Winding(s) Single, Multiple Taps No No Power - Max Varies Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 76.20mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 3.3 lbs (1.5kg)	Voltage - Secondary (Full Load)	10V, 20V, 40V
Secondary Winding(s) Center Tap No Power - Max Varies Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Wind Leads 1500Vrms 3.3 lbs (1.5kg)	Current - Output (Max)	750mA
Center TapNoPower - MaxVariesMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension63.50mm L x 76.20mm WHeight - Seated (Max)76.20mmVoltage - Isolation1500VrmsWeight3.3 lbs (1.5kg)	Primary Winding(s)	Single, Multiple Taps
Power - Max Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 76.20mm W Height - Seated (Max) 76.20mm Voltage - Isolation 1500Vrms Weight 3.3 lbs (1.5kg)	Secondary Winding(s)	Single, Multiple Taps
Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 76.20mm W Height - Seated (Max) 76.20mm Voltage - Isolation 1500Vrms Weight 3.3 lbs (1.5kg)	Center Tap	No
Termination Style Wire Leads Size / Dimension 63.50mm L x 76.20mm W Height - Seated (Max) 76.20mm Voltage - Isolation 1500Vrms Weight 3.3 lbs (1.5kg)	Power - Max	Varies
Size / Dimension63.50mm L x 76.20mm WHeight - Seated (Max)76.20mmVoltage - Isolation1500VrmsWeight3.3 lbs (1.5kg)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Weight 76.20mm 1500Vrms 3.3 lbs (1.5kg)	Termination Style	Wire Leads
Voltage - Isolation 1500Vrms Weight 3.3 lbs (1.5kg)	Size / Dimension	63.50mm L x 76.20mm W
Weight 3.3 lbs (1.5kg)	Height - Seated (Max)	76.20mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	3.3 lbs (1.5kg)
Report errors.		Report errors?

F-92A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F-92A Payment Methods





















F-92A Shipping Methods













If you have any question about F-92A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com