

F10-600-C2 Information



For Reference Only

Part Number F10-600-C2
Manufacturer Triad Magnetics
Category Transformers
Power Transformers

Description PC MOUNT CLASS 2 TRANSFORMER

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F10-600-C2 Specifications

Manufacturer Part NumberF10-600-C2ManufacturerTriad MagneticsCategoryTransformersPower TransformersPower TransformersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 1.2A, Series 600mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough Hole
Category Transformers Power Transformers Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA
Power Transformers Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA
Package - Control Package - Control Package - Control Package - Primary - Control Package - Primary - Courrent - Output (Max) - Parallel 5V, Series 10V - Parallel 1.2A, Series 600mA - Primary Winding(s) - Secondary Winding(s) - Secondary Winding(s) - Dual - Center Tap - No - No - Power - Max - Control Package - Primary - Package - Prima
Series - Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap Power - Max Polytham Secondary (Full Load) Parallel 1.2A, Series 600mA Parallel 1.2A, Series 600mA Power - Max A bound of VA
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5V, Series 10V Parallel 1.2A, Series 600mA Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Parallel 1.2A, Series 600mA Single Nu Dual Output Nu
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max6 VA
Secondary Winding(s)DualCenter TapNoPower - Max6 VA
Center Tap No Power - Max 6 VA
Power - Max 6 VA
Mounting Type Through Hole
Termination Style PC Pin
Size / Dimension 41.91mm L x 33.81mm W
Height - Seated (Max) 35.51mm
Voltage - Isolation 4200Vrms
Weight 0.44 lb (199.58g)
Report errors?

F10-600-C2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F10-600-C2 Payment Methods





















F10-600-C2 Shipping Methods













If you have any question about F10-600-C2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com