

### F10J100 Information

(A) Heisener.com

For Reference Only

Part Number F10J100
Manufacturer Ohmite
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 100 OHM 5% 10W

Package Radial, Flat Oval

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## F10J100 Specifications

Manufacturer Part Number  Manufacturer  Ohmite  Category  Resistors  Chassis Mount Resistors  Package  Radial, Flat Oval  Series  Stackohm? 250  Resistance  100 Ohms  Tolerance  ±5%  Power (Watts)  10W  Composition  Wirewound  Temperature Coefficient  ±260ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  - Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Flange Braces, Right Angle  Size / Dimension  Nessistors  Ohmite  Resistors  Chassis Mount Resistors  Radial, Flat Oval  Stackohm? 250  Package  Stackohm? 250  Chassis Mount Resistors  Chassis Mount Resistors  Chassis Mount Resistors  Chassis Mount Resistors  Package  Stackohm? 250  Stackohm? 250  Vitreous Enamel Coated  Flange Braces, Right Angle  Size / Dimension  0.750" L x 0.375" W (19.05mm x 9.53mm)
CategoryResistorsPackageRadial, Flat OvalSeriesStackohm? 250Resistance100 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)
Chassis Mount Resistors  Package Radial, Flat Oval  Series Stackohm? 250  Resistance 100 Ohms  Tolerance ±5%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C  Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Size / Dimension  Chassis Mount Resistors Radial, Flat Oval  Stackohm? 250  Watch Stackohm? 250  Stackohm? 250  Ladial, Flat Oval  Stackohm? 250  Stackohm? 250  Ladial, Flat Oval  Stackohm? 250  Stackohm? 250  Ladial, Flat Oval  La
PackageRadial, Flat OvalSeriesStackohm? 250Resistance100 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)
SeriesStackohm? 250Resistance100 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)
Resistance 100 Ohms  Tolerance ±5%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle  Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)
Tolerance ±5%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle  Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)
Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 260 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 350^{\circ}\text{C}$ Features-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension $0.750^{\circ}\text{L x } 0.375^{\circ}\text{W } (19.05 \text{mm x } 9.53 \text{mm})$
Composition  Wirewound  Temperature Coefficient  ±260ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  - Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Flange Braces, Right Angle  Size / Dimension  0.750" L x 0.375" W (19.05mm x 9.53mm)
Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle  Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)
Operating Temperature  -55°C ~ 350°C  Features  - Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Flange Braces, Right Angle  Size / Dimension  0.750" L x 0.375" W (19.05mm x 9.53mm)
Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)
Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Flange Braces, Right Angle  Size / Dimension  0.750" L x 0.375" W (19.05mm x 9.53mm)
Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)
Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)
H 1 1 C 1 1 M 1
Height - Seated (Max) 0.375" (9.53mm)
Lead Style Solder Lugs
Package / Case Radial, Flat Oval
Failure Rate -
Report errors?

### F10J100 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## F10J100 Payment Methods



















# F10J100 Shipping Methods













If you have any question about F10J100, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com