



F10J10R Information

(A) Heisener.com

For Reference Only

Part NumberF10J10RManufacturerOhmiteCategoryResistors

Chassis Mount Resistors

Description RES CHAS MNT 10 OHM 5% 10W

Package Radial, Flat Oval

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F10J10R Specifications

Manufacturer Part Number F10J10R Manufacturer Ohmite Category Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 10 Ohms Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	1 100 10K Specifications	
CategoryResistorsPackageRadial, Flat OvalSeriesStackohm? 250Resistance10 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Manufacturer Part Number	F10J10R
Chassis Mount Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 10 Ohms Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±400pm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Manufacturer	Ohmite
PackageRadial, Flat OvalSeriesStackohm? 250Resistance10 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Category	Resistors
SeriesStackohm? 250Resistance10 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-		Chassis Mount Resistors
Resistance10 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Package	Radial, Flat Oval
Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate	Series	Stackohm? 250
Power (Watts) Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Package / Case Radial, Flat Oval Failure Rate -	Resistance	10 Ohms
Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Tolerance	±5%
Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Power (Watts)	10W
Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate	Temperature Coefficient	±400ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.53mm) Rodard Lugs Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle Radial, Flat Oval Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle 1.750" L x 0.375" W (19.05mm x 9.53mm) Flange Braces, Right Angle Flange Bra	Features	-
Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate	Mounting Feature	Flange Braces, Right Angle
Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Size / Dimension	0.750" L x 0.375" W (19.05mm x 9.53mm)
Package / Case Radial, Flat Oval Failure Rate -	Height - Seated (Max)	0.375" (9.53mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Flat Oval
Report errors?	Failure Rate	-
		Report errors?

F10J10R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F10J10R Payment Methods





















F10J10R Shipping Methods













If you have any question about F10J10R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com