

F10J15R Information

(Heisener.com

For Reference Only

Part Number F10J15R
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 15 OHM 5% 10W

Package Radial, Flat Oval

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F10J15R Specifications

Manufacturer Part NumberF10J15RManufacturerOhmiteCategoryResistorsPackageRadial, Flat OvalSeriesStackohm? 250Resistance15 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-		
CategoryResistorsPackageRadial, Flat OvalSeriesStackohm? 250Resistance15 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Manufacturer Part Number	F10J15R
Chassis Mount Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 15 Ohms Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate	Manufacturer	Ohmite
PackageRadial, Flat OvalSeriesStackohm? 250Resistance15 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Heigh - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Category	Resistors
SeriesStackohm? 250Resistance15 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-		Chassis Mount Resistors
Resistance 15 Ohms Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Package	Radial, Flat Oval
Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Series	Stackohm? 250
Power (Watts) Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Package / Case Radial, Flat Oval Failure Rate -	Resistance	15 Ohms
Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Tolerance	±5%
Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Power (Watts)	10W
Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Temperature Coefficient	±400ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.53mm) Solder Lugs Package / Case Radial, Flat Oval	Features	-
Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate 0.375" (9.53mm) Solder Lugs Radial, Flat Oval	Mounting Feature	Flange Braces, Right Angle
Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Size / Dimension	0.750" L x 0.375" W (19.05mm x 9.53mm)
Package / Case Radial, Flat Oval Failure Rate -	Height - Seated (Max)	0.375" (9.53mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Flat Oval
Report errors?	Failure Rate	-
1		Report errors?

F10J15R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F10J15R Payment Methods

































If you have any question about F10J15R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com