



### F10J600E Information

Man Cate

Part Number F10J600E
Manufacturer Ohmite
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 600 OHM 5% 10W

Package Radial, Flat Oval

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## F10J600E Specifications

Manufacturer         Ohmite           Category         Resistors           Chassis Mount Resistors           Package         Radial, Flat Oval           Series         Stackohm? 250           Resistance         600 Ohms           Tolerance         ±5%           Power (Watts)         10W           Composition         Wirewound           Temperature Coefficient         ±260ppm/°C           Operating Temperature         -55°C ~ 350°C           Features         -           Coating, Housing Type         Vitreous Enamel Coated           Mounting Feature         Flange Braces, Right Angle           Size / Dimension         0.750" L x 0.375" W (19.05mm x 9.53mm)           Height - Seated (Max)         0.375" (9.53mm)           Lead Style         Solder Lugs           Package / Case         Radial, Flat Oval	1 103000L Specifications	
Category  Resistors  Chassis Mount Resistors  Package  Radial, Flat Oval  Series  Stackohm? 250  Resistance  600 Ohms  Tolerance  ±5%  Power (Watts)  10W  Composition  Wirewound  Temperature Coefficient  ±260ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  - Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Flange Braces, Right Angle  Size / Dimension  0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max)  0.375" (9.53mm)  Lead Style  Package / Case  Radial, Flat Oval	Manufacturer Part Number	F10J600E
Chassis Mount Resistors  Package Radial, Flat Oval  Series Stackohm? 250  Resistance 600 Ohms  Tolerance ±5%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle  Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max) 0.375" (9.53mm)  Lead Style Solder Lugs  Package / Case Radial, Flat Oval	Manufacturer	Ohmite
Package Radial, Flat Oval Series Stackohm? 250  Resistance 600 Ohms  Tolerance ±5%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C  Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max) 0.375" (9.53mm)  Lead Style Solder Lugs  Package / Case Radial, Flat Oval	Category	Resistors
Series         Stackohm? 250           Resistance         600 Ohms           Tolerance         ±5%           Power (Watts)         10W           Composition         Wirewound           Temperature Coefficient         ±260ppm/°C           Operating Temperature         -55°C ~ 350°C           Features         -           Coating, Housing Type         Vitreous Enamel Coated           Mounting Feature         Flange Braces, Right Angle           Size / Dimension         0.750" L x 0.375" W (19.05mm x 9.53mm)           Height - Seated (Max)         0.375" (9.53mm)           Lead Style         Solder Lugs           Package / Case         Radial, Flat Oval		Chassis Mount Resistors
Resistance 600 Ohms Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval	Package	Radial, Flat Oval
Tolerance ±5%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle  Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max) 0.375" (9.53mm)  Lead Style Solder Lugs  Package / Case Radial, Flat Oval	Series	Stackohm? 250
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±260ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  -  Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Flange Braces, Right Angle  Size / Dimension  0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max)  0.375" (9.53mm)  Lead Style  Package / Case  Radial, Flat Oval	Resistance	600 Ohms
Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle  Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max) 0.375" (9.53mm)  Lead Style Solder Lugs  Package / Case Radial, Flat Oval	Tolerance	±5%
Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max) 0.375" (9.53mm)  Lead Style Solder Lugs  Package / Case Radial, Flat Oval	Power (Watts)	10W
Operating Temperature  -55°C ~ 350°C  Features  - Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Flange Braces, Right Angle Size / Dimension  0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max)  0.375" (9.53mm)  Lead Style  Package / Case  Radial, Flat Oval	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max) 0.375" (9.53mm)  Lead Style Solder Lugs  Package / Case Radial, Flat Oval	Temperature Coefficient	±260ppm/°C
Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Flange Braces, Right Angle  0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max)  0.375" (9.53mm)  Lead Style  Solder Lugs  Package / Case  Radial, Flat Oval	Operating Temperature	-55°C ~ 350°C
Mounting Feature  Flange Braces, Right Angle  Size / Dimension  0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max)  0.375" (9.53mm)  Lead Style  Solder Lugs  Package / Case  Radial, Flat Oval	Features	-
Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)  Height - Seated (Max) 0.375" (9.53mm)  Lead Style Solder Lugs  Package / Case Radial, Flat Oval	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max)  Lead Style  Package / Case  0.375" (9.53mm)  Solder Lugs  Radial, Flat Oval	Mounting Feature	Flange Braces, Right Angle
Lead Style Solder Lugs Package / Case Radial, Flat Oval	Size / Dimension	0.750" L x 0.375" W (19.05mm x 9.53mm)
Package / Case Radial, Flat Oval	Height - Seated (Max)	0.375" (9.53mm)
	Lead Style	Solder Lugs
Failure Rate	Package / Case	Radial, Flat Oval
1 unuto 1 tuto	Failure Rate	-
Report errors?		Report errors?

### F10J600E Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# F10J600E Payment Methods





















## F10J600E Shipping Methods













If you have any question about F10J600E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com