

F16-400-C2-B Information



For Reference Only

Part Number F16-400-C2-B

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description XFRMR LAMINATED 6VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F16-400-C2-B Specifications

Manufacturer Part Number F16-400-C2-B Manufacturer Triad Magnetics Category Transformers Package - Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)		
Category Transformers Package - Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Manufacturer Part Number	F16-400-C2-B
Power Transformers Package - Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Manufacturer	Triad Magnetics
Package - Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) Parallel 8V, Series 16 V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Category	Transformers
Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation Weight 115V Parallel 8V, Series 16V Pa	Series	Split Pack?, Class 2/3, F
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 8V, Series 16V Parallel 8V, Series 400mA Primary Winding(s) Single Dual Center Tap No 6 VA Mounting Type Through Hole Termination Style 9C Pin 41.28mm L x 33.32mm W 4200Vrms	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 800mA, Series 400mA Single Dual Poul No Power No 4 VA 4	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Voltage - Secondary (Full Load)	Parallel 8V, Series 16V
Secondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)33.32mmVoltage - Isolation4200VrmsWeight0.44 lb (199.58g)	Current - Output (Max)	Parallel 800mA, Series 400mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)33.32mmVoltage - Isolation4200VrmsWeight0.44 lb (199.58g)	Primary Winding(s)	Single
Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Power - Max	6 VA
Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 33.32mm 4200Vrms 0.44 lb (199.58g)	Termination Style	PC Pin
Voltage - Isolation 4200Vrms Weight 0.44 lb (199.58g)	Size / Dimension	41.28mm L x 33.32mm W
Weight 0.44 lb (199.58g)	Height - Seated (Max)	33.32mm
	Voltage - Isolation	4200Vrms
Report errors?	Weight	0.44 lb (199.58g)
		Report errors?

F16-400-C2-B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F16-400-C2-B Payment Methods



















F16-400-C2-B Shipping Methods













If you have any question about F16-400-C2-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com