

F16-800 Information



For Reference Only

Part Number F16-800

ManufacturerTriad MagneticsCategoryTransformers

Power Transformers

Description XFRMR LAMINATED THRU HOLE

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F16-800 Specifications

Manufacturer Part NumberF16-800ManufacturerTriad MagneticsCategoryTransformersPackage-SeriesSplit Pack?, Class 2/3, FTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 1.6A, Series 800mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)2500VrmsVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)		
Category Transformers Power Transformers Package Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Voltage - Isolation Tansformers Power Transformers Aphower Transformers Parminator Style Transformers Power Transformers Aphower Transformers Parmination Style Through Hole PC Pin 36.50mm Voltage - Isolation Voltage - Isolation Do No Isolation Transformers Power Transformers Parminator Style Through Hole PC Pin 36.50mm Voltage - Isolation Voltage - Isolation Do No Isolation No Isolation Parmination Style Transformers Power Transformer Power Transforme	Manufacturer Part Number	F16-800
Package Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) Voltage - Isolation Veight Voltage - Isolation Power Tansformers Split Pack?, Class 2/3, F Laminated Core Parllel 1.6A, Series 800mA Parallel 1.6A, Series 800mA Parallel 1.6A, Series 800mA Primary Winding(s) Single Parallel 1.6A, Series 800mA Parallel 1.6A, Series 16V Parallel 1.6A, Series 1	Manufacturer	Triad Magnetics
Package - Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight	Category	Transformers
SeriesSplit Pack?, Class 2/3, FTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)Parallel 8V, Series 16 VCurrent - Output (Max)Parallel 1.6A, Series 800mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)36.50mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight	Series	Split Pack?, Class 2/3, F
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 8V, Series 16V Parallel 1.6A, Series 800mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Parallel 8V, Series 16V Parallel 8V, Series 16V Parallel 8V, Series 16V Parallel 1.6A, Series 800mA Single Pual No 2500Vrms 0.7 lb (317.51g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension Voltage - Isolation Voltage - Isolation Parallel 1.6A, Series 800mA Single Dual Powal Poul No	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight O.7 lb (317.51g)	Voltage - Secondary (Full Load)	Parallel 8V, Series 16V
Secondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)36.50mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Current - Output (Max)	Parallel 1.6A, Series 800mA
Center TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)36.50mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Center Tap	No
Termination Style PC Pin Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Power - Max	12 VA
Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 36.50mm 2500Vrms 0.7 lb (317.51g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Size / Dimension	47.63mm L x 39.67mm W
Weight 0.7 lb (317.51g)	Height - Seated (Max)	36.50mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.7 lb (317.51g)
		Report errors?

F16-800 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F16-800 Payment Methods



















F16-800 Shipping Methods













If you have any question about F16-800, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com