

F161ZS124K630V

F161ZS124K630V Information

| Heisener.com | Part Number Manufacturer Category Description Package | F161ZS124K630V KEMET Capacitors Film Capacitors CAP FILM 0.12UF 630VDC SMD Nonstandard SMD For the pricing/inventory/lead time, please contact | |
|--------------------|---|--|-----------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



F161ZS124K630V Specifications

| ManufacturerKEMETCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageNonstandard SMDSeriesF161Capacitance0.12µFTolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedSER (Equivalent Series Resistance)-Operating Temperature.55°C ~ 125°CVoltage / CaseNonstandard SMDStackage / CaseNonstandard SMDSize / Dimension0.650° L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features- | | | |
|---|------------------------------------|---|----------------|
| CategoryCapacitorsPackageNonstandard SMDSeriesF161Capacitance0.12µFTolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedStrigg Temperature-5°C ~ 125°CMounting TypeSurface MountSize / Dimension0.650° L x 0.591°W (16.50mm x 15.00mm)Height - Seated (Max)0.283°(7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Seatures-Starter Startes-Starter Startes-Starter Startes-Starter Startes-Starter Starter-Starter Starter Starter-Starter Starter Starter-St | Manufacturer Part Number | F161ZS124K630V | |
| Film CapacitorsPackageNonstandard SMDSeriesF161Capacitance0.12µFTolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)Cherral Package in Agament-ApplicationsGeneral PurposeFeatures- | Manufacturer | KEMET | |
| PackageNonstandard SMDSeriesF161Capacitance0.12µFTolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Category | Capacitors | |
| Series F161 Capacitance 0.12µF Tolerance ±10% Voltage Rating - AC 250V Voltage Rating - DC 630V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case Nonstandard SMD Size / Dimension 0.650" L x 0.591" W (16.50mm x 15.00mm) Height - Seated (Max) 0.283" (7.20mm) Termination Solder Pads Lead Spacing - Applications General Purpose Features - | | Film Capacitors | |
| Capacitance0.12µFTolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Package | Nonstandard SMD | |
| Tolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Series | F161 | |
| Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Capacitance | 0.12µF | |
| Voltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Tolerance | ±10% | |
| Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Voltage Rating - AC | 250V | |
| ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Voltage Rating - DC | 630V | |
| Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Dielectric Material | Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked | |
| Mounting TypeSurface MountPackage / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | ESR (Equivalent Series Resistance) | - | |
| Package / CaseNonstandard SMDSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Operating Temperature | -55°C ~ 125°C | |
| Size / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Mounting Type | Surface Mount | |
| Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Package / Case | Nonstandard SMD | |
| TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Size / Dimension | 0.650" L x 0.591" W (16.50mm x 15.00mm) | |
| Lead Spacing-ApplicationsGeneral PurposeFeatures- | Height - Seated (Max) | 0.283" (7.20mm) | |
| ApplicationsGeneral PurposeFeatures- | Termination | Solder Pads | |
| Features - | Lead Spacing | - | |
| | Applications | General Purpose | |
| Report errors? | Features | - | |
| | | | Report errors? |

F161ZS124K630V Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

F161ZS124K630V Payment Methods



If you have any question about F161ZS124K630V, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com