

# F161ZS474K400V

#### F161ZS474K400V Information

-			

Part Number	F161ZS474K400V
Manufacturer	KEMET
Category	Capacitors Film Capacitors
Description	CAP FILM 0.47UF 10% 400VDC SMD
Package	Nonstandard
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## F161ZS474K400V Specifications

Manufacturer KEMET   Capacitors Film Capacitors   Package Nonstandard   Series Nonstandard   Capacitance 0.47µF   Yoltage Rating - AC 200V   Voltage Rating - DC 400V   Dielectric Material Polyestr, Polyethylene Terephthalate (PET), Metallized - Stacked   Operating Temperature -   Voltage Acid (Max) Stafkard   Size / Dimension Nonstandard   Size / Dimension Octor L x 0.591" W (16.50mm x 15.00mm)   Height - Seated (Max) Solder Pads   Applications Solder Pads   Applications General Purpose   Applications General Purpose			
CategoryCapacitorsPackageNonstandardPackageNonstandardSeriesF161Capacitance0.47µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedSESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CNonstandardSurface MountSize / Dimension0.650° L x 0.591°W (16.50mm x 15.00mm)Height - Seated (Max)0.283° (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Starter Series-Starter Series </td <td>Manufacturer Part Number</td> <td>F161ZS474K400V</td> <td></td>	Manufacturer Part Number	F161ZS474K400V	
Film CapacitorsPackageNonstandardSeriesF161Capacitance0.47μFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)Charler PadsSolder PadsLead Spacing-Features-Features-	Manufacturer	KEMET	
PackageNonstandardSeriesFl61Capacitance0.47μFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating TemperatureSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Category	Capacitors	
Series F161   Capacitance 0.47µF   Tolerance ±10%   Voltage Rating - AC 200V   Voltage Rating - DC 400V   Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked   ESR (Equivalent Series Resistance) -   Operating Temperature -55°C ~ 125°C   Mounting Type Surface Mount   Package / Case Nonstandard   Size / Dimension 0.650" L x 0.591" W (16.50mm x 15.00mm)   Height - Seated (Max) 0.283" (7.20mm)   Lead Spacing -   Applications General Purpose   Features -		Film Capacitors	
Capacitance0.47µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package	Nonstandard	
Tolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	F161	
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	0.47µF	
Voltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650° L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	$\pm 10\%$	
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	200V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	400V	
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked	
Mounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseNonstandardSize / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C	
Size / Dimension0.650" L x 0.591" W (16.50mm x 15.00mm)Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount	
Height - Seated (Max)0.283" (7.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	Nonstandard	
TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.650" L x 0.591" W (16.50mm x 15.00mm)	
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.283" (7.20mm)	
ApplicationsGeneral PurposeFeatures-	Termination	Solder Pads	
Features -	Lead Spacing	-	
	Applications	General Purpose	
Report errors?	Features	-	
			Report errors?

#### F161ZS474K400V Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## F161ZS474K400V Payment Methods



If you have any question about F161ZS474K400V, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com