

F20-120-C2

F20-120-C2 Information

Heisener.com	F20-120-C2 Triad Magnetics Transformers Power Transformers PC MOUNT CLASS 2 TRANSFORMER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



F20-120-C2 Specifications

ManufacturerTriad MagneticsCategoryTransformersPower TransformersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)SinglePrimary Winding(s)SingleSecondary Winding(s)DualPower - Max.5 VAMounting TypeThrough HolePomer - MaxSingleSing - Secondary LingSingleSecondary Specific AdditionSinglePower - Max.5 VAMounting TypeSingle - SingleMounting TypeSingle - SingleSing - Secondary LingSingleMaunting TypeSingleMaunting TypeSingleMaunting TypeSingleSing - SingleSingleSingle - SingleSingleSingle - SolationMagnetific AdditionMaunting TypeSingleSingle - Single - SingleSingleSingle - Single - Sing		
CategoryTransformersPower TransformersPackagePackageSeries-TypeLaminated CoreVoltage - PrimaryVoltage - Secondary (Full Load)Parallel 10V, Series 20VVoltage - Secondary (Full Load)Parallel 240mA, Series 120mACurrent - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)Secondary Winding(s)DualCenter TapPower - MaxAnounting TypeThrough HoleSize / DimensionSize / DimensionHeight - Seated (Max)Voltage - IsolationWeightWeightState (Max)State (Max)State (Max)Set (Max)State (Max) <td>Manufacturer Part Number</td> <td>F20-120-C2</td>	Manufacturer Part Number	F20-120-C2
Power TransformersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleSize / DimensionS5.51mm L x 30.51mm WHeight - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Manufacturer	Triad Magnetics
Package-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypePrinagh HoleTermination StyleScinm L x 30.51mm WSize / Dimension3.551mm L x 30.51mm WVoltage - Isolation4.00VrmsWeightScing Li 13.4g)	Category	Transformers
Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StyleScinm L x 30.51mm WSize / Dimension32.00mmVoltage - Isolation4200VrmsWeight0.51b (113.4g)		Power Transformers
TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StyleS1.51mm L x 30.51mm WSize / Dimension32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Package	-
Yoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StyleSc1mm L x 30.51mm WSize / Dimension32.00mmHeight - Seated (Max)32.00mmWottage - Isolation0.25 lb (113.4g)	Series	-
Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StyleSc11mm L x 30.51mm WSize / Dimension32.00mmHeight - Seated (Max)4200VrmsWoltage - Isolation0.25 lb (113.4g)	Туре	Laminated Core
Current - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.51mm L x 30.51mm WHeight - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.51mm L x 30.51mm WHeight - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.51mm L x 30.51mm WHeight - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Current - Output (Max)	Parallel 240mA, Series 120mA
Center TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.51mm L x 30.51mm WHeight - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Primary Winding(s)	Single
Power - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.51mm L x 30.51mm WHeight - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension35.51mm L x 30.51mm WHeight - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Center Tap	No
Termination StylePC PinSize / Dimension35.51mm L x 30.51mm WHeight - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Power - Max	2.5 VA
Size / Dimension 35.51mm L x 30.51mm W Height - Seated (Max) 32.00mm Voltage - Isolation 4200Vrms Weight 0.25 lb (113.4g)	Mounting Type	Through Hole
Height - Seated (Max)32.00mmVoltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Termination Style	PC Pin
Voltage - Isolation4200VrmsWeight0.25 lb (113.4g)	Size / Dimension	35.51mm L x 30.51mm W
Weight 0.25 lb (113.4g)	Height - Seated (Max)	32.00mm
- -	Voltage - Isolation	4200Vrms
Report errors?	Weight	0.25 lb (113.4g)
		Report errors?

F20-120-C2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about F20-120-C2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com