

F20J40K Information

Heisener.com

For Reference Only

Part Number F20J40K
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 40K OHM 5% 20W

Package Radial, Flat Oval

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F20J40K Specifications

Manufacturer Part Number Manufacturer Ohmite Category Resistors Chassis Mount Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 40 kOhms Colerance ±5% Power (Watts) Composition Wirewound Femperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Coating, Housing Type Vitreous Enamel Coated
Category Resistors Chassis Mount Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 40 kOhms Folerance ±5% Power (Watts) Composition Wirewound Femperature Coefficient Departing Temperature -55°C ~ 350°C Features
Chassis Mount Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 40 kOhms Folerance ±5% Power (Watts) Composition Wirewound Temperature Coefficient Departing Temperature -55°C ~ 350°C Features Chassis Mount Resistors Radial, Flat Oval Stackohm? 250 Wirewound ±5% -55°C ~ 350°C -55°C ~ 350°C
Package Radial, Flat Oval Series Stackohm? 250 Resistance 40 kOhms Tolerance ±5% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features -
Series Stackohm? 250 Resistance 40 kOhms Folerance $\pm 5\%$ Power (Watts) 20W Composition Wirewound Femperature Coefficient ± 260 ppm/°C Operating Temperature -55 °C ~ 350 °C Features -
Resistance 40 kOhms Folerance $\pm 5\%$ Power (Watts) $20W$ Composition Wirewound Temperature Coefficient $\pm 260 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 350^{\circ}\text{C}$ Features $-$
Folerance $\pm 5\%$ Power (Watts) 20W Composition Wirewound Femperature Coefficient $\pm 260 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 350^{\circ}\text{C}$ Features -
Power (Watts) 20W Composition Wirewound Temperature Coefficient $\pm 260 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 350^{\circ}\text{C}$ Features -
Composition Wirewound Temperature Coefficient $\pm 260 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 350^{\circ}\text{C}$ Features -
Temperature Coefficient $\pm 260 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 350^{\circ}\text{C}$ Features $-$
Operating Temperature -55°C ~ 350°C - Features -
Features -
Coating, Housing Type Vitreous Enamel Coated
Mounting Feature Flange Braces, Right Angle
Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm)
Height - Seated (Max) 0.375" (9.53mm)
Lead Style Solder Lugs
Package / Case Radial, Flat Oval
Failure Rate -
Report errors?

F20J40K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F20J40K Payment Methods





















F20J40K Shipping Methods













If you have any question about F20J40K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com