

F20J4K0 Information

(A) Heisener.com

Part Number F20J4K0
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 4K OHM 5% 20W

Package Radial, Flat Oval

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F20J4K0 Specifications

For Reference Only

Manufacturer Part Number F20J4K0 Manufacturer Ohmite Category Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 4 kOhms Tolerance ±5% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -		
Category Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 4 kOhms Tolerance ±5% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Manufacturer Part Number	F20J4K0
Chassis Mount Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 4 kOhms Tolerance ±5% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate	Manufacturer	Ohmite
PackageRadial, Flat OvalSeriesStackohm? 250Resistance4 kOhmsTolerance±5%Power (Watts)20WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Category	Resistors
SeriesStackohm? 250Resistance4 kOhmsTolerance±5%Power (Watts)20WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-		Chassis Mount Resistors
Resistance 4 kOhms Tolerance ±5% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Package	Radial, Flat Oval
Tolerance ±5% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Series	Stackohm? 250
Power (Watts) Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Resistance	4 kOhms
Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Tolerance	±5%
Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Power (Watts)	20W
Operating Temperature Features Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Temperature Coefficient	±260ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Features	-
Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate 0.375" (9.53mm) Solder Lugs Radial, Flat Oval	Mounting Feature	Flange Braces, Right Angle
Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Size / Dimension	0.750" L x 0.375" W (19.05mm x 9.53mm)
Package / Case Radial, Flat Oval Failure Rate -	Height - Seated (Max)	0.375" (9.53mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Flat Oval
Report errors?	Failure Rate	-
		Report errors?

F20J4K0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F20J4K0 Payment Methods



















F20J4K0 Shipping Methods













If you have any question about F20J4K0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com