

F3-24 Information



For Reference Only

Part Number F3-24

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description XFRMR LAMINATED THRU HOLE

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F3-24 Specifications

| Manufacturer Part Number Manufacturer Category Transformers Power Transformers Power Transformers Package - Series Quick Pack Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) 24V Current - Output (Max) Primary Winding(s) Single Secondary Winding(s) Single Secondary Winding(s) Single Center Tap Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Tansformers Power - Max Magnetics Transformers Power - Laminated Core Uits Valve Laminated Core Uits Valve Laminated Core Voltage - Secondary (Full Load) 24V Current - Output (Max) Single Center Tap Yes Power - Max August Connect - 0.187" (4.7mm) Size / Dimension 41 28mm L x 30 15mm W | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|----------------------------------------|
| Category Power Transformers Package - Series Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Tarnsformers Public Center Tansformers Power Transformers Power Transformers Power Transformers Public Power Transformers Public Power Transformers Public Power Transformers Power Transformers Public Power Transformers Power Transformers Public Power Transformers P | Manufacturer Part Number | F3-24 |
| Package Series Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Power - Max Mounting Type Chassis Mount Termination Style Power - 0.187" (4.7mm) | Manufacturer | Triad Magnetics |
| Package - Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 100mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 2.4 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) | Category | Transformers |
| Series Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 100mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 2.4 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) | | Power Transformers |
| Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 100mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 2.4 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) | Package | - |
| Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style 115V 115V 100mA 100mA Single Single Single Center Tap Yes Power - Max Solder, Quick Connect - 0.187" (4.7mm) | Series | Quick Pack |
| Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max August 2.4 VA Mounting Type Chassis Mount Termination Style Z4V Single Single Yes Center Tap Yes Solder, Quick Connect - 0.187" (4.7mm) | Туре | Laminated Core |
| Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max And Sundang Sundang Chassis Mount Termination Style 100mA Single Single 2.4 VA Chassis Mount Solder, Quick Connect - 0.187" (4.7mm) | Voltage - Primary | 115V |
| Primary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max 2.4 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) | Voltage - Secondary (Full Load) | 24V |
| Secondary Winding(s) Center Tap Yes Power - Max 2.4 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) | Current - Output (Max) | 100mA |
| Center TapYesPower - Max2.4 VAMounting TypeChassis MountTermination StyleSolder, Quick Connect - 0.187" (4.7mm) | Primary Winding(s) | Single |
| Power - Max 2.4 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) | Secondary Winding(s) | Single |
| Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) | Center Tap | Yes |
| Termination Style Solder, Quick Connect - 0.187" (4.7mm) | Power - Max | 2.4 VA |
| · | Mounting Type | Chassis Mount |
| Size / Dimension 41.28mm L. x 30.15mm W | Termination Style | Solder, Quick Connect - 0.187" (4.7mm) |
| Size / Dimension | Size / Dimension | 41.28mm L x 30.15mm W |
| Height - Seated (Max) 30.15mm | Height - Seated (Max) | 30.15mm |
| Voltage - Isolation 2500VAC | Voltage - Isolation | 2500VAC |
| Weight 0.25 lb (113.4g) | Weight | 0.25 lb (113.4g) |
| Report errors? | | Report errors? |

F3-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F3-24 Payment Methods



















F3-24 Shipping Methods













If you have any question about F3-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com