

# F36-550-C2

uest a Quote

### F36-550-C2 Information

| Part Number  | F36-550-C2  |  |
|--------------|---|--|
| Manufacturer | Triad Magnetics   |  |
| Category     | Transformers<br>Power Transformers  |  |
| Description  | PC MOUNT CLASS 2 TRANSFORMER  |  |
| Package      | -   |  |
|              | For the pricing/inventory/lead time, please contact                       |  |
|              | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com |  |
|              | Manufacturer<br>Category<br>Description                                   |  |

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## F36-550-C2 Specifications

| ManufacturerTriad MagneticsCategoryTriad MagneticsCategoryFower TransformersPackage-Series-Stries-TypeLaminated CoreVoltage - PrimaryI15VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeFrinough HoleSize / DimensionStol1mm L x 48.51mm WSize / Dimension88.51mmVoltage - Isolation4200Vrms   |                                 |                             |
|--|---------------------------------|-----------------------------|
| CategoryTransformersPackage-Package-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleSize / DimensionS8.01mm L x 48.51mm WSize / Dimension38.51mmVoltage - Isolation0.8 lb (362.87g)   | Manufacturer Part Number        | F36-550-C2                  |
| PackagePower TransformersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleSize / Dimension58.01mm L x 48.51mm WSize / Dimension38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)  | Manufacturer                    | Triad Magnetics             |
| Package-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StyleSell 180, Sell 180 | Category                        | Transformers                |
| Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StyleS8.01mm L x 48.51mm WSize / Dimension38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)  |                                 | Power Transformers          |
| TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StyleSecondary Minding(s)Size / DimensionS8.01mm L x 48.51mm WHeight - Seated (Max)38.51mmWeight0.8 lb (362.87g)   | Package                         | -                           |
| Yoltage - Primary115VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StyleS8.01mm L x 48.51mm WSize / Dimension38.51mmHeight - Seated (Max)4200VrmsWeight0.8 lb (362.87g)   | Series                          | -                           |
| Voltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StyleSecondary Minding(s)Size / DimensionS8.01mm L x 48.51mm WHeight - Seated (Max)38.51mmWoltage - IsolationQ0 VrmsWeight0.8 lb (362.87g)  | Туре                            | Laminated Core              |
| Current - Output (Max)Parallel 1.1A, Series 550mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension58.01mm L x 48.51mm WHeight - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)  | Voltage - Primary               | 115V                        |
| Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension58.01mm L x 48.51mm WHeight - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)   | Voltage - Secondary (Full Load) | Parallel 18V, Series 36V    |
| Secondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension58.01mm L x 48.51mm WHeight - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)   | Current - Output (Max)          | Parallel 1.1A, Series 550mA |
| Center TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension58.01mm L x 48.51mm WHeight - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)   | Primary Winding(s)              | Single                      |
| Power - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension58.01mm L x 48.51mm WHeight - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)   | Secondary Winding(s)            | Dual                        |
| Mounting TypeThrough HoleTermination StylePC PinSize / Dimension58.01mm L x 48.51mm WHeight - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)   | Center Tap                      | No                          |
| Termination StylePC PinSize / Dimension58.01mm L x 48.51mm WHeight - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)  | Power - Max                     | 20 VA                       |
| Size / Dimension58.01mm L x 48.51mm WHeight - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)   | Mounting Type                   | Through Hole                |
| Height - Seated (Max)38.51mmVoltage - Isolation4200VrmsWeight0.8 lb (362.87g)  | Termination Style               | PC Pin                      |
| Voltage - Isolation4200VrmsWeight0.8 lb (362.87g)  | Size / Dimension                | 58.01mm L x 48.51mm W       |
| Weight 0.8 lb (362.87g)  | Height - Seated (Max)           | 38.51mm                     |
|  | Voltage - Isolation             | 4200Vrms                    |
| Report errors?   | Weight                          | 0.8 lb (362.87g)            |
|  |                                 | Report errors?              |

#### F36-550-C2 Guarantees



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# F36-550-C2 Payment Methods



## F36-550-C2 Shipping Methods



If you have any question about F36-550-C2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com