

F56-045 Information



For Reference Only

Part Number F56-045

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description XFRMR LAMINATED THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F56-045 Specifications

Manufacturer F56-045 Manufacturer Triad Magnetics Category Transformers Package - Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 28 V, Series 56V Current - Output (Max) Parallel 90mA, Series 45mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 2500Vrms Weight 0.25 lb (113.4g)		
Category Transformers Power Transformers Package - Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 28 V, Series 56V Current - Output (Max) Parallel 90mA, Series 45mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 2500Vrms Weight 0.25 lb (113.4g)	Manufacturer Part Number	F56-045
Package Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 28 V, Series 56V Current - Output (Max) Parallel 90mA, Series 45mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 2500Vrms Weight Woltage - Isolation 2500Vrms Weight	Manufacturer	Triad Magnetics
Package - Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 28 V, Series 56V Current - Output (Max) Parallel 90mA, Series 45mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 2500Vrms Weight	Category	Transformers
Series Split Pack?, Class 2/3, F Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) Parallel 28 V, Series 56 V Current - Output (Max) Parallel 90mA, Series 45mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 2500 Vrms Weight 0.25 lb (113.4g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 28 V, Series 56V Current - Output (Max) Parallel 90mA, Series 45mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 2500Vrms Weight 0.25 lb (113.4g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 28 V, Series 56V Current - Output (Max) Parallel 90mA, Series 45mA Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 115V Parallel 28 V, Series 56V Single Single No 2.5 VA Mounting Type Through Hole Termination Style 2.5 VA 30.15mm Voltage - Isolation Voltage - Isolation 0.25 lb (113.4g)	Series	Split Pack?, Class 2/3, F
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 28 V, Series 56V Parallel 90mA, Series 45mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 90mA, Series 45mA Single Pound Single Pound No Powal Pound No Pound Pound No Po	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) Voltage - Isolation Veight Single Single Single No 2.5 VA No 2.5 VA Through Hole PC Pin 34.93mm L x 28.58mm W 30.15mm Voltage - Isolation 2500Vrms 0.25 lb (113.4g)	Voltage - Secondary (Full Load)	Parallel 28 V, Series 56V
Secondary Winding(s) Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 0.25 lb (113.4g)	Current - Output (Max)	Parallel 90mA, Series 45mA
Center TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.15mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Primary Winding(s)	Single
Power - Max 2.5 VA Mounting Type Through Hole PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) Voltage - Isolation Veight 2.5 VA 2.5 VA 2.5 VA 2.5 VA 2.5 VA PC Pin 34.93mm L x 28.58mm W 30.15mm 4.900vrms	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) Voltage - Isolation Weight O.25 lb (113.4g)	Center Tap	No
Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 2500Vrms Weight 0.25 lb (113.4g)	Power - Max	2.5 VA
Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 2500Vrms Weight 0.25 lb (113.4g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 30.15mm 2500Vrms 0.25 lb (113.4g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 0.25 lb (113.4g)	Size / Dimension	34.93mm L x 28.58mm W
Weight 0.25 lb (113.4g)	Height - Seated (Max)	30.15mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.25 lb (113.4g)
		Report errors?

F56-045 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F56-045 Payment Methods



















F56-045 Shipping Methods













If you have any question about F56-045, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com