

F58000206 Information

Heisener.com

Part Number F58000206

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Position Sensors - Angle, Linear Position Measuring

Description POS TRANS-XDCR LT 6 IN 6K/1.0%

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F58000206 Specifications

Manufacturer Part Number F58000206 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package - Series LT For Measuring Linear Position Technology Resistive Rotation Angle - Electrical, Mechanical - Linear Range 0 ~ 152.40mm (0 ~ 6.00") Output Resistive Output Signal - Actuator Type Round Shaft Linearity ±1% Resistance 6 kOhms Resistance Tolerance ±20% Voltage - Supply 30V Mounting Type Custom Termination Style Wire Leads Operating Temperature -40°C ~ 80°C		
Category Sensors, Transducers Position Sensors - Angle, Linear Position Measuring Package LT For Measuring Linear Position Technology Resistive Rotation Angle - Electrical, Mechanical Linear Range 0 ~ 152.40mm (0 ~ 6.00") Output Resistive Output Signal - Actuator Type Round Shaft Linearity Elinearity Resistance 6 kOhms Resistance 7 kOthers Resistance 6 kOhms Resistance 7 custom Nounting Type Custom Termination Style Operating Temperature Sensors, Transducers Position Sensors - Angle, Linear Position Measuring Position Sensors - Angle, Linear Position Measuring Position Sensors - Angle, Linear Position Measuring Actual Position Measuring Resistive 1 timear Position Resistive 1 timear Posi	Manufacturer Part Number	F58000206
Package - Series LT For Measuring Linear Position Technology Resistive Rotation Angle - Electrical, Mechanical - Linear Range 0 ~ 152.40mm (0 ~ 6.00") Output Resistive Output Signal - Actuator Type Round Shaft Linearity ±1% Resistance 6 kOhms Resistance 10erance ±20% Voltage - Supply 30V Mounting Type Custom Termination Style Wire Leads Operating Temperature 4 40°C ~ 80°C	Manufacturer	Honeywell Sensing and Productivity Solutions
Package - Series LT For Measuring Linear Position Technology Resistive Rotation Angle - Electrical, Mechanical - Linear Range 0 ~ 152.40mm (0 ~ 6.00") Output Resistive Output Signal - Actuator Type Round Shaft Linearity ±1% Resistance 6 kOhms Resistance Tolerance ±20% Voltage - Supply 30V Mounting Type Custom Termination Style Wire Leads Operating Temperature -40°C ~ 80°C	Category	Sensors, Transducers
SeriesLTFor MeasuringLinear PositionTechnologyResistiveRotation Angle - Electrical, Mechanical-Linear Range0 ~ 152.40mm (0 ~ 6.00")OutputResistiveOutput Signal-Actuator TypeRound ShaftLinearity±1%Resistance6 kOhmsResistance Tolerance±20%Voltage - Supply30VMounting TypeCustomTermination StyleWire LeadsOperating Temperature-40°C ~ 80°C		Position Sensors - Angle, Linear Position Measuring
For Measuring Technology Resistive Rotation Angle - Electrical, Mechanical Linear Range 0 ~ 152.40mm (0 ~ 6.00") Output Resistive Output Signal - Actuator Type Round Shaft Linearity ±1% Resistance 6 kOhms Resistance 7 ok Voltage - Supply 30V Mounting Type Custom Termination Style Operating Temperature Linear Position Linear Position Resistive 0 ~ 152.40mm (0 ~ 6.00") Resistive 0 ~ 152.40mm (0 ~ 6.00") Resistive 0 ~ 152.40mm (0 ~ 6.00") 0 ~ 15	Package	-
TechnologyResistiveRotation Angle - Electrical, Mechanical-Linear Range0 ~ 152.40mm (0 ~ 6.00")OutputResistiveOutput Signal-Actuator TypeRound ShaftLinearity±1%Resistance6 kOhmsResistance Tolerance±20%Voltage - Supply30VMounting TypeCustomTermination StyleWire LeadsOperating Temperature-40°C ~ 80°C	Series	LT
Rotation Angle - Electrical, Mechanical Linear Range 0 ~ 152.40mm (0 ~ 6.00") Output Resistive Output Signal - Actuator Type Round Shaft Linearity ±1% Resistance 6 kOhms Resistance Tolerance ±20% Voltage - Supply 30V Mounting Type Custom Termination Style Operating Temperature -40°C ~ 80°C	For Measuring	Linear Position
Linear Range $0 \sim 152.40 \text{mm} (0 \sim 6.00")$ OutputResistiveOutput Signal-Actuator TypeRound ShaftLinearity $\pm 1\%$ Resistance 6 kOhms Resistance Tolerance $\pm 20\%$ Voltage - Supply 30V Mounting TypeCustomTermination StyleWire LeadsOperating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Technology	Resistive
Output Signal Actuator Type Round Shaft Linearity Esistance Resistance Resistance Coltrance Co	Rotation Angle - Electrical, Mechanical	-
Output Signal - Actuator Type Round Shaft Linearity $\pm 1\%$ Resistance 6 kOhms Resistance Tolerance $\pm 20\%$ Voltage - Supply 30V Mounting Type Custom Termination Style Wire Leads Operating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Linear Range	0 ~ 152.40mm (0 ~ 6.00")
Actuator TypeRound ShaftLinearity $\pm 1\%$ Resistance 6 kOhms Resistance Tolerance $\pm 20\%$ Voltage - Supply 30V Mounting TypeCustomTermination StyleWire LeadsOperating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Output	Resistive
Linearity $\pm 1\%$ Resistance 6 kOhms Resistance Tolerance $\pm 20\%$ Voltage - Supply 30V Mounting Type Custom Termination Style Wire Leads Operating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Output Signal	-
Resistance 6 kOhms Resistance Tolerance $\pm 20\%$ Voltage - Supply 30V Mounting TypeCustomTermination StyleWire LeadsOperating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Actuator Type	Round Shaft
Resistance Tolerance $\pm 20\%$ Voltage - Supply $30V$ Mounting TypeCustomTermination StyleWire LeadsOperating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Linearity	$\pm 1\%$
Voltage - Supply $30V$ Mounting TypeCustomTermination StyleWire LeadsOperating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Resistance	6 kOhms
Mounting Type Custom Termination Style Wire Leads Operating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Resistance Tolerance	±20%
Termination Style Wire Leads Operating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Voltage - Supply	30V
Operating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Mounting Type	Custom
	Termination Style	Wire Leads
Dopost owners?	Operating Temperature	-40°C ~ 80°C
Report errors?		Report errors?

F58000206 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F58000206 Payment Methods



















F58000206 Shipping Methods













If you have any question about F58000206, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com