

FA18X8R1H222KNU06

FA18X8R1H222KNU06 Information



Part Number FA18X8R1H222KNU06

Manufacturer TDK Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 2200PF 50V X8R RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FA18X8R1H222KNU06 Specifications

Manufacturer Part Number FA18X8R1H222KNU06 Manufacturer TDK Corporation Category Capacitors Package Radial Series FA Capacitance 2200pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X8R Operating Temperature -55°C ~ 150°C Features High Temperature Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads		
Category Capacitors Package Radial Series FA Capacitance 2200pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X8R Operating Temperature -55°C ~ 150°C Features High Temperature Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Manufacturer Part Number	FA18X8R1H222KNU06
Package Radial Series FA Capacitance 2200pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X8R Operating Temperature -55°C ~ 150°C Features High Temperature Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Manufacturer	TDK Corporation
Package Radial Series FA Capacitance 2200pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X8R Operating Temperature -55°C ~ 150°C Features High Temperature Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Category	Capacitors
Series FA Capacitance 2200pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X8R Operating Temperature -55°C ~ 150°C Features High Temperature Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads		Ceramic Capacitors
Capacitance 2200pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X8R Operating Temperature -55°C ~ 150°C Features High Temperature Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Package	Radial
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X8R Operating Temperature -55°C ~ 150°C Features High Temperature Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Series	FA
Voltage - Rated50VTemperature CoefficientX8ROperating Temperature-55°C ~ 150°CFeaturesHigh TemperatureRatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.217" (5.50mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleFormed Leads	Capacitance	2200pF
Temperature Coefficient Operating Temperature -55°C ~ 150°C Features High Temperature AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style X8R AEC-Q200 Automotive - High Temperature Automotive Automotive - Automotive - High Temperature Automotive - High Temperature Automotive - Lead Spocing Automotive - Lead Syacing Automotive Automotive - Lead Syacing Automotive - Lead Syacing Automotive - Lead Syacing Automotive Automotive - Lead Syacing Automotive - Lead Syacing Automotive Automotive - Lead Syacing Automotive Automotive - Lead Syacing Automoti	Tolerance	±10%
Operating Temperature-55°C ~ 150°CFeaturesHigh TemperatureRatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.217" (5.50mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleFormed Leads	Voltage - Rated	50V
Features High Temperature Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Temperature Coefficient	X8R
Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Operating Temperature	-55°C ~ 150°C
Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Features	High Temperature
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Ratings	AEC-Q200
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Applications	Automotive
Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Failure Rate	-
Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.217" (5.50mm) - Lead Spacing 0.098" (2.50mm) Formed Leads	Package / Case	Radial
Thickness (Max) Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads	Size / Dimension	0.157" L x 0.098" W (4.00mm x 2.50mm)
Lead Spacing0.098" (2.50mm)Lead StyleFormed Leads	Height - Seated (Max)	0.217" (5.50mm)
Lead Style Formed Leads	Thickness (Max)	-
•	Lead Spacing	0.098" (2.50mm)
Report errors?	Lead Style	Formed Leads
		Report errors?

FA18X8R1H222KNU06 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FA18X8R1H222KNU06 Payment Methods



















FA18X8R1H222KNU06 Shipping Methods













If you have any question about FA18X8R1H222KNU06, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com