

FAN5622SX Information



For Reference Only

Part Number FAN5622SX

Manufacturer ON Semiconductor

Category Integrated Circuits (ICs)
PMIC - LED Drivers

Description IC LED DRIVER LINEAR DIM 6SSOT

Package SOT-23-6 Thin, TSOT-23-6

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FAN5622SX Specifications

Manufacturer Part Number FAN5622SX Manufacturer ON Semiconductor Category Integrated Circuits (ICs) PMIC - LED Drivers Package SOT-23-6 Thin, TSOT-23-6 Series - Type Linear Topology - Internal Switch(s) Yes Number of Outputs 2 Voltage - Supply (Min) 2.7V Voltage - Supply (Max) 5.5V Voltage - Output - Current - Output / Channel 30mA Frequency - Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot		
Category Integrated Circuits (ICs) PMIC - LED Drivers Package SOT-23-6 Thin, TSOT-23-6 Series - Type Linear Topology - Internal Switch(s) Yes Number of Outputs 2 Voltage - Supply (Min) 2.7V Voltage - Supply (Max) 5.5V Voltage - Output - Current - Output / Channel 30mA Frequency - Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Manufacturer Part Number	FAN5622SX
Package SOT-23-6 Thin, TSOT-23-6 Series - Type Linear Topology - Internal Switch(s) Yes Number of Outputs 2 2 Voltage - Supply (Min) 2.7V Voltage - Supply (Max) 5.5V Voltage - Output - Current - Output / Channel 30mA Frequency - Dimming Single-Wire Applications Backlight Operating Temperature 4-0°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SUPSON SOT - 23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Manufacturer	ON Semiconductor
PackageSOT-23-6 Thin, TSOT-23-6Series-TypeLinearTopology-Internal Switch(s)YesNumber of Outputs2Voltage - Supply (Min)2.7VVoltage - Supply (Max)5.5VVoltage - Output-Current - Output / Channel30mAFrequency-DimmingSingle-WireApplicationsBacklightOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6 Thin, TSOT-23-6Supplier Device Package6-SuperSot	Category	Integrated Circuits (ICs)
Series-TypeLinearTopology-Internal Switch(s)YesNumber of Outputs2Voltage - Supply (Min)2.7VVoltage - Supply (Max)5.5VVoltage - Output-Current - Output / Channel30mAFrequency-DimmingSingle-WireApplicationsBacklightOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6 Thin, TSOT-23-6Supplier Device Package6-SuperSot		PMIC - LED Drivers
Type Linear Topology - Internal Switch(s) Yes Number of Outputs 2 Voltage - Supply (Min) 2.7V Voltage - Supply (Max) 5.5V Voltage - Output / Channel 30mA Frequency - Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Package	SOT-23-6 Thin, TSOT-23-6
Topology - Internal Switch(s) Yes Number of Outputs 2 Voltage - Supply (Min) 2.7V Voltage - Supply (Max) 5.5V Voltage - Output - Output / Channel 30mA Frequency - Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Series	-
Internal Switch(s)YesNumber of Outputs2Voltage - Supply (Min)2.7VVoltage - Supply (Max)5.5VVoltage - Output-Current - Output / Channel30mAFrequency-DimmingSingle-WireApplicationsBacklightOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6 Thin, TSOT-23-6Supplier Device Package6-SuperSot	Туре	Linear
Number of Outputs Voltage - Supply (Min) 2.7V Voltage - Supply (Max) 5.5V Voltage - Output - Current - Output / Channel Frequency Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case Supplier Device Package 6-SuperSot	Topology	-
Voltage - Supply (Min) 2.7V Voltage - Supply (Max) 5.5V Voltage - Output - Current - Output / Channel Frequency - Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case Supplier Device Package 6-SuperSot	Internal Switch(s)	Yes
Voltage - Supply (Max) Voltage - Output Current - Output / Channel Frequency Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case Supplier Device Package 6-SuperSot	Number of Outputs	2
Voltage - Output Current - Output / Channel Frequency - Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package	Voltage - Supply (Min)	2.7V
Current - Output / Channel 30mA Frequency - Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Voltage - Supply (Max)	5.5V
Frequency - Dimming Single-Wire Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Voltage - Output	-
DimmingSingle-WireApplicationsBacklightOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6 Thin, TSOT-23-6Supplier Device Package6-SuperSot	Current - Output / Channel	30mA
Applications Backlight Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Frequency	-
Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Dimming	Single-Wire
Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Applications	Backlight
Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package 6-SuperSot	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$
Supplier Device Package 6-SuperSot	Mounting Type	Surface Mount
	Package / Case	SOT-23-6 Thin, TSOT-23-6
Report errors?	Supplier Device Package	6-SuperSot
		Report errors?

FAN5622SX Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FAN5622SX Payment Methods



















FAN5622SX Shipping Methods













If you have any question about FAN5622SX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com