

FCA-210-0917M Information



For Reference Only

Part Number FCA-210-0917M

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FCA-210-0917M Specifications

Manufacturer Part NumberFCA-210-0917MManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysPackage-SeriesMilitary, MIL-R-83536/9, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.75 VDCOperate Time10msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMilitary, MIL-R-83536/9, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.75 VDCOperate Time10msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer Part Number	FCA-210-0917M
Package-SeriesMilitary, MIL-R-83536/9, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.75 VDCOperate Time10msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-R-83536/9, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.75 VDCOperate Time10msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Category	Relays
SeriesMilitary, MIL-R-83536/9, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.75 VDCOperate Time10msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.75 VDCOperate Time10msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 10ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Series	Military, MIL-R-83536/9, FCA, CII
Coil Current Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 10ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 10ms Release Time 10ms Release Time Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 10ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Current	-
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max 1urn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 10ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Voltage	12VDC
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 10ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 10ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Switching Voltage	115VAC, 28VDC - Max
Operate Time10msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Turn On Voltage (Max)	9 VDC
Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn Off Voltage (Min)	0.75 VDC
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Operate Time	10ms
Mounting Type Chassis Mount Termination Style Solder Hook	Release Time	10ms
Termination Style Solder Hook	Features	Sealed - Hermetically
•	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Hook
		Report errors?

FCA-210-0917M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FCA-210-0917M Payment Methods



















FCA-210-0917M Shipping Methods













If you have any question about FCA-210-0917M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com