

FCA-410-1622M Information



For Reference Only

Part Number FCA-410-1622M

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 10A 28V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FCA-410-1622M Specifications

Manufacturer Part NumberFCA-410-1622MManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMilitary, MIL-R-83536/16, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePlug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMilitary, MIL-R-83536/16, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePlug In	Manufacturer Part Number	FCA-410-1622M
Package - Series Military, MIL-R-83536/16, FCA, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-R-83536/16, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePlug In	Category	Relays
SeriesMilitary, MIL-R-83536/16, FCA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePlug In	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Series	Military, MIL-R-83536/16, FCA, CII
Coil Current Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Release Time 5eatures Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Coil Current	-
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style	Coil Voltage	28VDC
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Contact Rating (Current)	10A
Turn Off Voltage (Min) 1.5 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Switching Voltage	115VAC, 28VDC - Max
Operate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePlug In	Turn On Voltage (Max)	18 VDC
Release Time 15ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Turn Off Voltage (Min)	1.5 VDC
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Plug In	Operate Time	15ms
Mounting Type Chassis Mount Termination Style Plug In	Release Time	15ms
Termination Style Plug In	Features	Sealed - Hermetically
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Plug In
		Report errors?

FCA-410-1622M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FCA-410-1622M Payment Methods



















FCA-410-1622M Shipping Methods













If you have any question about FCA-410-1622M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com