

FCB-205-0227M Information



For Reference Only

Part Number FCB-205-0227M

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 28V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FCB-205-0227M Specifications

Manufacturer Part NumberFCB-205-0227MManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMilitary, MIL-R-83536/2, FCB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMilitary, MIL-R-83536/2, FCB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePC Pin	Manufacturer Part Number	FCB-205-0227M
Package - Series Military, MIL-R-83536/2, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Purpose	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-R-83536/2, FCB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePC Pin	Category	Relays
SeriesMilitary, MIL-R-83536/2, FCB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage28VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PDC	Series	Military, MIL-R-83536/2, FCB, CII
Coil Current Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Coil Current	-
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Coil Voltage	28VDC
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Switching Voltage	115VAC, 28VDC - Max
Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Turn Off Voltage (Min)	1.5 VDC
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style PC Pin	Operate Time	5ms
Mounting Type Chassis Mount Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Hermetically
·	Mounting Type	Chassis Mount
Report errors?	Termination Style	PC Pin
		Report errors?

FCB-205-0227M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FCB-205-0227M Payment Methods



















FCB-205-0227M Shipping Methods













If you have any question about FCB-205-0227M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com