

FCB-405-0620M Information



For Reference Only

Part Number FCB-405-0620M

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 5A 28V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FCB-405-0620M Specifications

Manufacturer Part Number Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Power Relays, Over 2 Amps Package Series Military, MIL-R-83536/6, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max
Category Relays Power Relays, Over 2 Amps Package - Series Military, MIL-R-83536/6, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Power Relays, Over 2 Amps Package Series Military, MIL-R-83536/6, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Package - Series Military, MIL-R-83536/6, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Series Military, MIL-R-83536/6, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Coil Current - Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Coil Voltage 28VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max
Switching Voltage 115VAC, 28VDC - Max
Turn On Voltage (Max) 18 VDC
Turn Off Voltage (Min) 1.5 VDC
Operate Time 6ms
Release Time 6ms
Features Sealed - Hermetically
Mounting Type Chassis Mount
Termination Style PC Pin
Report errors

FCB-405-0620M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FCB-405-0620M Payment Methods



















FCB-405-0620M Shipping Methods













If you have any question about FCB-405-0620M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com