

# FCC17A15PB400

a Quote

### FCC17A15PB400 Information

Heisener.com	Part Number	FCC17A15PB400	
	Manufacturer	Amphenol Commercial Products	ि वि र
	Category	Connectors, Interconnects D-Sub Connectors	- 233
	Description	CONN D-SUB PLUG 15POS R/A SOLDER	- 6424
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only			
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Requ

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# FCC17A15PB400 Specifications

Manufacturer     Amphenol Commercial Products       Category     Connectors, Interconnects       D-Sub Connectors     D-Sub Connectors       Package     -       Series     FCC17       Connector Style     D-Sub Connectors       Connector Type     Plug, Male Pins       Number of Positions     15       Number of Rows     2       Shell Size, Connector Layout     2 (DA, A)       Contact Type     Signal       Mounting Type     Through Hole, Right Angle       Flange Feature     Board Lock, Filter, Grounding Indents       Features     Soder       Shell Material, Finish     Steel, Tin Plated       Contact Finish Thickness     Ipin (0.38µm)		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesFCC17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15 (Did Stein)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	FCC17A15PB400
D-Sub ConnectorsPackage-SeriesFCC17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15 juin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesFCC17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessJipin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesFCC17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesSteel, Tin PlatedShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	FCC17
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleHousing/Shell (4-40)SolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeaturesHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Filter, Grounding Indents
Contact Finish Thickness 15µin (0.38µm)   Ingress Protection -   Material Flammability Rating UL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	15µin (0.38µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### FCC17A15PB400 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### FCC17A15PB400 Payment Methods



## FCC17A15PB400 Shipping Methods



If you have any question about FCC17A15PB400, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com