

# FCC17A15PC240

a Quote

### FCC17A15PC240 Information

Heisener.com	Part Number	FCC17A15PC240	
	Manufacturer	Amphenol Commercial Products	
	Category	Connectors, Interconnects D-Sub Connectors	5
	Description	CONN D-SUB PLUG 15POS R/A SOLDER	- E
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	R

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## FCC17A15PC240 Specifications

Amplenol Commercial Products   Category Connectors, Interconnects   D-Sub Connectors D-Sub Connectors   Package -   Series FCC17   Connector Style D-Sub Connectors   Connector Type Plug, Male Pins   Number of Positions 15   Number of Rows 2   Shell Size, Connector Layout Signal   Mounting Type Housing/Shell (Unthreaded)   Flange Feature Solder   Flange Features Solder   Shell Material, Finish Steel, Tin Plated   Contact Finish Thickness Gold   Contact Finish Thickness Sipin (0.38µm)		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesFCC17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Stell Size, Connector Layout2 (DA, A)Contact TypeSignalMouning TypeFhough Hole, Right AngleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15 (Di A)Contact Finish ThicknessSuel Juin PlatedContact Finish ThicknessSuel Juin PlatedContact Finish Thickness15 (Di A)Material Flammability RatingUL94 V-0	Manufacturer Part Number	FCC17A15PC240
D-Sub ConnectorsPackage-SeriesFCC17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15 juin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesFCC17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessJui (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesFCC17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15 juin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)FeaturesSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	FCC17
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Filter, Grounding Indents
Contact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	15µin (0.38µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### FCC17A15PC240 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### FCC17A15PC240 Payment Methods



## FCC17A15PC240 Shipping Methods



If you have any question about FCC17A15PC240, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com