

FCE17B25PB450

FCE17B25PB450 Information

C Heisener.com	 FCE17B25PB450 Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 25POS R/A SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FCE17B25PB450 Specifications

Manufacturer Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors Package - Series FCE17 Connector Style D-Sub Connectors Connector Style D-Sub Connectors Connector Style Plug, Male Pins Connector Style 25 Number of Positions 3 (DB, B) Contact Type Signal Mounting Type Signal Flange Feature Housing/Shell (4-40) Features Solder Features Solder Shell Material, Finish Steel, Tin Plated Contact Finish Thickness Gold Contact Finish Thickness Signi (0.38µm)		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesFCE17Connector StyleD-Sub Connector StyleConnector TypePlug, Male PinsConnector Type2Number of Positions2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMouning TypeFhough Hole, Right AngleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress ProtectionJL94 V-0	Manufacturer Part Number	FCE17B25PB450
D-Sub ConnectorsPackage-SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessJuji (U.38µm)Atterial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	FCE17
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIojuin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	25
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeaturesHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Filter, Grounding Indents
Contact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	15µin (0.38µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

FCE17B25PB450 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FCE17B25PB450 Payment Methods



FCE17B25PB450 Shipping Methods



If you have any question about FCE17B25PB450, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com