

# FCE17B25PB490

t a Quote

### FCE17B25PB490 Information

Heisener.com	Part Number	FCE17B25PB490	
	Manufacturer	Amphenol Commercial Products	
	Category	Connectors, Interconnects D-Sub Connectors	E
	Description	CONN D-SUB PLUG 25POS R/A SOLDER	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Re

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# FCE17B25PB490 Specifications

ManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesFCE17Connector StyleD-Sub Connector StyleConnector TypePlug, Male PinsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessJipin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMouting TypeSignalFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish Thickness15µin (0.38µm)Ingress ProtectionVL94 V-0	Manufacturer Part Number	FCE17B25PB490
PackageD-Sub ConnectorsPackage-SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessJipin (0.38µm)Atterial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	FCE17
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	25
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Filter, Grounding Indents
Contact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	15µin (0.38µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### FCE17B25PB490 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### FCE17B25PB490 Payment Methods



## FCE17B25PB490 Shipping Methods



If you have any question about FCE17B25PB490, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com