

FCE17C37PB200

t a Quote

FCE17C37PB200 Information

Heisener.com	Part Number	FCE17C37PB200	
	Manufacturer	Amphenol Commercial Products	
	Category	Connectors, Interconnects D-Sub Connectors	- 24
	Description	CONN D-SUB PLUG 37POS R/A SOLDER	_ 100
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		US Websites https://www.bsissurgeous	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Rec

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FCE17C37PB200 Specifications

Manufacturer Part NumberFCE I7C37PB200ManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsPackage-SeriesFCE I7Connector StyleD-Sub ConnectorConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Schell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Auterial Flammability RatingUdy Vo		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeHousing/Shell (Unthreaded)Flange FeatureSolderFlange FeaturesSolderShell Material, FinishSteel, Tin PlatedContact FinishGoldContact FinishSignalMaterial Flanmability RatingUL94 V-0	Manufacturer Part Number	FCE17C37PB200
D-Sub ConnectorsPackage-SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)FeaturesSolderShell Material, FinishStel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-O	Manufacturer	Amphenol Commercial Products
Package.SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)FeaturesSoderShell Material, FinishSiel, Tin PlatedContact FinishGoldContact Finish Thickness1.5 µin (0.38µm)Ingress Protection.Material Flanmability RatingUL94 Yo	Category	Connectors, Interconnects
SeriesFCE17Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldKontact Finish ThicknessJuju (J.Sugm)Ingress Protection-Material Flanmability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flanmability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Filter, Grounding IndentsFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	FCE17
Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIspin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	37
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 You	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Filter, Grounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Filter, Grounding Indents
Contact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	15μin (0.38μm)
	Ingress Protection	-
	Material Flammability Rating	UL94 V-0
Report errors?		Report errors?

FCE17C37PB200 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FCE17C37PB200 Payment Methods



FCE17C37PB200 Shipping Methods



If you have any question about FCE17C37PB200, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com