

# FCP1206H682G-H1

#### FCP1206H682G-H1 Information

and the oner, com	 FCP1206H682G-H1 Cornell Dubilier Electronics (CDE) Capacitors Film Capacitors CAP FILM 6800PF 2% 50VDC 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### FCP1206H682G-H1 Specifications

Manufacturer Part NumberFCP1206H682G-H1ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsFilm CapacitorsFilm CapacitorsPackage1206 (3216 Metric)SeriesFCPCapacitance6800pFTolerance±2%Voltage Rating - AC50VDielectric MaterialPolyphenylene Sulfide (PPS)Dielectric Material-Operating Temperature-Operating TypeSurface MountSize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.09mm)TerminationSolder Pads		
CategoryCapacitorsFilm CapacitorsPackage1206 (3216 Metric)SeriesFCPCapacitance6800pFCapacitange±2%Yoltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CMounting TypeSulface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)Solder PadsYoltage Rating - DCSolder Pads	Manufacturer Part Number	FCP1206H682G-H1
Him CapacitorsPackage1206 (3216 Metric)SeriesFCPCapacitance6800pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)Solder Pads	Manufacturer	Cornell Dubilier Electronics (CDE)
Package1206 (3216 Metric)SeriesFCPCapacitance6800pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)Solder Pads	Category	Capacitors
SeriesFCPCapacitance6800pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)Solder PadsTerminationSolder Pads		Film Capacitors
Capacitance6800pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)Solder PadsYerminationSolder Pads	Package	1206 (3216 Metric)
Tolerance±2%Yoltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.09mm)Your Surface PackageSolder Package	Series	FCP
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.09mm)YerminationSolder Pads	Capacitance	6800pF
Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.09mm)FerminationSolder Pads	Tolerance	$\pm 2\%$
Dielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.09mm)TerminationSolder Pads	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.09mm)TerminationSolder Pads	Voltage Rating - DC	50V
Operating Temperature -55°C ~ 125°C   Mounting Type Surface Mount   Package / Case 1206 (3216 Metric)   Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)   Height - Seated (Max) 0.043" (1.09mm)   Termination Solder Pads	Dielectric Material	Polyphenylene Sulfide (PPS)
Mounting Type Surface Mount   Package / Case 1206 (3216 Metric)   Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)   Height - Seated (Max) 0.043" (1.09mm)   Termination Solder Pads	ESR (Equivalent Series Resistance)	-
Package / Case 1206 (3216 Metric)   Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)   Height - Seated (Max) 0.043" (1.09mm)   Termination Solder Pads	Operating Temperature	-55°C ~ 125°C
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)   Height - Seated (Max) 0.043" (1.09mm)   Termination Solder Pads	Mounting Type	Surface Mount
Height - Seated (Max)0.043" (1.09mm)TerminationSolder Pads	Package / Case	1206 (3216 Metric)
Termination Solder Pads	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
	Height - Seated (Max)	0.043" (1.09mm)
	Termination	Solder Pads
Lead Spacing -	Lead Spacing	-
Applications High Frequency, Switching	Applications	High Frequency, Switching
Features -	Features	-
Report errors?		Report errors?

#### FCP1206H682G-H1 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### FCP1206H682G-H1 Payment Methods





If you have any question about FCP1206H682G-H1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com