

FCP1210H333J-G3

FCP1210H333J-G3 Information

Www.neisener.com	 FCP1210H333J-G3 Cornell Dubilier Electronics (CDE) Capacitors Film Capacitors CAP FILM 0.033UF 5% 50VDC 1210 1210 (3225 Metric) For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FCP1210H333J-G3 Specifications

Manufacturer Cornell Dubilier Electronics (CDE) Category Capacitors Film Capacitors Film Capacitors Package 1210 (3225 Metric) Series FCP Capacitance 0.033µF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 50V Dielectric Material Polyphenylene Sulfide (PPS) ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.091" (2.30mm) Film Capacitors Solder Pads Lead Spacing - Applications High Frequency, Switching		
CategoryCapacitorsFilm CapacitorsPackage1210 (3225 Metric)SeriesFCPCapacitance0.033µFColerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)Dielectric Material-Operating Temperature-55°C ~ 125°CVoltage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-Statures-	Manufacturer Part Number	FCP1210H333J-G3
Fin CapacitorsPackage1210 (3225 Metric)SeriesFCPCapacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126° L x 0.098° W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Cornell Dubilier Electronics (CDE)
Package1210 (325 Metric)SeriesFCPCapacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.091" (2.30mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
SeriesFCPCapacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)Dielectric Material-Coperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.091" (2.30mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-Features-Features-		Film Capacitors
Capacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.091" (2.30mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Package	1210 (3225 Metric)
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.091" (2.30mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Series	FCP
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	0.033µF
Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	±5%
Dielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)	Voltage Rating - DC	50V
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polyphenylene Sulfide (PPS)
Notified TypeSurface MountMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	-55°C ~ 125°C
Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Surface Mount
Height - Seated (Max)0.091" (2.30mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	1210 (3225 Metric)
Termination Solder Pads Lead Spacing - Applications High Frequency, Switching Features -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing-ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	0.091" (2.30mm)
Applications High Frequency, Switching Features -	Termination	Solder Pads
Features -	Lead Spacing	-
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

FCP1210H333J-G3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

FCP1210H333J-G3 Payment Methods



FCP1210H333J-G3 Shipping Methods



If you have any question about FCP1210H333J-G3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com