



Heisener.com

FFA.0S.304.CLAC42Z Information

Part Number FFA.0S.304.CLAC42Z

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN INLINE PLUG 4PIN SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FFA.0S.304.CLAC42Z Specifications

Manufacturer Part Number FFA.0S.304.CLAC42Z Manufacturer LEMO Category Connectors, Interconnects Package - Series 0S Connector Type Plug, Female Sockets and Male Pins Number of Positions 4 Shell Size - Insert 304 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A		
CategoryConnectors, InterconnectsPackage-Series0SConnector TypePlug, Female Sockets and Male PinsNumber of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Manufacturer Part Number	FFA.0S.304.CLAC42Z
Package-Series0SConnector TypePlug, Female Sockets and Male PinsNumber of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Manufacturer	LEMO
Package-Series0SConnector TypePlug, Female Sockets and Male PinsNumber of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Category	Connectors, Interconnects
SeriesOSConnector TypePlug, Female Sockets and Male PinsNumber of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A		Circular Connectors
Connector Type Plug, Female Sockets and Male Pins Number of Positions 4 Shell Size - Insert 304 Shell Size, MIL	Package	-
Number of Positions4Shell Size - Insert304Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Series	OS
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets and Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Number of Positions	4
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Shell Size - Insert	304
Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Termination	Solder Cup
Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Orientation	Keyed
Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Ingress Protection	IP50 - Dust Protected
Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 7A	Contact Finish	Gold
Current Rating 7A	Features	Backshell, Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7A
		Report errors?

FFA.0S.304.CLAC42Z Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FFA.0S.304.CLAC42Z Payment Methods



















FFA.0S.304.CLAC42Z Shipping Methods













If you have any question about FFA.0S.304.CLAC42Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com